

THE MAGIC HOUR

FLEXFORM™ LVT - Atmosphere and Perspective

Luxury Vinyl Tile

Construction

High Performance Luxury Vinyl Tile

Finish

ProGuard™ MAX Coating

Wear Layer Thickness

22 mil (0.55 mm)

Overall Thickness

5.0 mm (0.197")

Edge Profile

Straight

Critical Radiant Flux (ASTM E648)

Pass - Class I

Smoke Density (ASTM E662)

Pass - ≤ 450

Flexibility (ASTM F137)

Pass

Static Coefficient of Friction (ASTM D2047)

Pass

Dynamic Coefficient of Friction (ANSI A137)

Pass

Resistance to Chemicals (ASTM F925)

Pass

Installation

Direct Glue

Tile Sizes

Perspective:

25 cm x 150 cm (9.84" x 59.06")

Atmosphere:

50 cm x 50 cm (19.7" x 19.7")

Pieces Per Box

Perspective: 6

Atmosphere: 10

Weight Per Box

Perspective: 46 lb (20.87 kg)

Atmosphere: 50.9 lb (23.1 kg)

Quantity Per Box

Perspective: 24.22 ft² (2.25 m²)

Atmosphere: 26.91 ft² (2.5 m²)

Recommended Installation Method

Random

WARRANTIES

22 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions.

ADHESIVE

For more information on our adhesive options, please visit our website.

See installation instructions for more information on adhesive use.



Declare.



M/PACT™
CARBON NEUTRAL PROGRAM