

# THE MAGIC HOUR

## FLEXFORM™ LVT - Horizon

Luxury Vinyl Tile

### Construction

High Performance Luxury Vinyl Tile

### Finish

ProGuard™ MAX Coating

### Wear Layer Thickness

22 mil (0.55 mm)

### Overall Thickness

5.0 mm (0.197")

### Edge Profile

Straight

### Critical Radiant Flux (ASTM E648)

Pass - Class I

### Smoke Density (ASTM E662)

Pass - ≤ 450

### Flexibility (ASTM F137)

Pass

### Static Coefficient of Friction (ASTM D2047)

Pass

### Dynamic Coefficient of Friction (ANSI A137)

Pass

### Resistance to Chemicals (ASTM F925)

Pass

### Installation

Direct Glue

### Tile Size

25 cm x 150 cm (9.84" x 59.06")

### Pieces Per Box

6

### Weight Per Box

46 lb (20.87 kg)

### Quantity Per Box

24.22 ft² (2.25 m²)

### Recommended Installation Method

Random

### WARRANTIES

22 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions.

### ADHESIVE

For more information on our adhesive options, please visit our website.

See installation instructions for more information on adhesive use.



Declare.



M/PACT™  
CARBON NEUTRAL PROGRAM