

ALL TOGETHER NOW

RIGIDFORM™ LVT

Luxury Vinyl Tile

Construction

High Performance Rigid Core Tile

Finish

ProGuard™ Coating

Wear Layer Thickness

22 mil (0.56 mm) and 12 mil (0.3 mm)

Overall Thickness

5.0 mm (0.2")

Integrated Pad

1.0 mm XPO

Edge Profile

Micro Bevel, with secure locking mechanism

Critical Radiant Flux (ASTM E648)

Pass - Class I

Smoke Density (ASTM E662)

Pass - ≤ 450

Flexibility (ASTM F137)

Pass

Static Coefficient of Friction (ASTM D2047)

Pass

Dynamic Coefficient of Friction (ANSI A137)

Pass

Resistance to Chemicals (ASTM F925)

Pass

Installation

Floating floor

ASTM E492 IIC Rating

56 (6" no drop ceiling)

59 (8" no drop ceiling)

51 (18" OWT with ceiling)

ASTM E90 STC Rating

50 (6" no drop ceiling)

55 (8" no drop ceiling)

58 (18" OWT with ceiling)

ASTM E2179 Δ IIC Rating

24 (6" no drop ceiling)

ASTM 3222 HIIC Rating

58 (6" no drop ceiling)

62 (8" no drop ceiling)

62 (18" OWT with ceiling)

Tile Size

7.56" x 48.62"

9.13" x 60.31"

Pieces Per Box

7.56" x 48.62": 10

9.13" x 60.31": 7

Weight Per Box

7.56" x 48.62": 44.8 lb (20.32 kg)

9.13" x 60.31": 47.0 lb (21.32 kg)

Quantity Per Box7.56" x 48.62": 25.52 ft² (2.37 m²)9.13" x 60.31": 26.78 ft² (2.49 m²)**Recommended Installation Method**

Random

WARRANTIES

22 mil Wear Layer: 15 Year Limited Commercial Wear

12 mil Wear Layer: 10 Year Limited Light Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions.


Declare.

ORTHO-PHTHALATE
FREE



M/PACT™
CARBON NEUTRAL PROGRAM