

# MERGE FORWARD

## RIGIDFORM FREE™ Resilient

Resilient Tile

### GENERAL

**Construction**

PVC-Free Acoustic Rigid Core Tile

**Finish**

ProGuard MAX™ Coating

**Overall /Wear Layer Thickness** 4.5 mm/20 mil

**Integrated Pad**

1.0 mm IXPE pad

**Edge Profile**

Tongue and Groove

### PERFORMANCE

**Critical Radiant Flux (ASTM E648)**

Pass - Class I

**Smoke Density (ASTM E662)**

Pass - ≤ 450

**Resistance to Heat (ASTM F1514)**

Pass

**Resistance to Light (ASTM F1515)**

Pass

**Resistance to Chemicals (ASTM F925)**

Pass

**Static Coefficient of Friction (ASTM D2047)**

Pass

**Dynamic Coefficient of Friction (ANSI A137)**

Pass

**ASTM E492 IIC Rating**

55 (6" no drop ceiling)

60 (8" no drop ceiling)

51 (18" OWT with ceiling)

### SUSTAINABILITY

**Embodied Carbon**
8.3 (kg CO<sub>2</sub>e)/m<sup>2</sup>

### TILE/PLANK SIZE

**Tile/Plank Size**

High Ground: 7" x 48"

Rejuvenate: 18" x 36"

### SHIPPING

**Pieces Per Box**

7" x 48" planks: 14

18" x 36" tiles: 7

**Weight Per Box**

7" x 48" planks: 39.82 lb (18.06 kg)

18" x 36" tiles: 38.45 lb (17.44 kg)

**Quantity Per Box**
7" x 48" planks: 32.67 ft<sup>2</sup> (3.04 m<sup>2</sup>)18" x 36" tiles: 31.50 ft<sup>2</sup> (2.93 m<sup>2</sup>)
**Quantity Per Pallet/Container**

7" x 48" planks:

65 cartons/pallet 2,123.35 ft<sup>2</sup>14 pallets/container 29,726 ft<sup>2</sup>

18" x 36" planks:

42 cartons/pallet 1,323 ft<sup>2</sup>20 pallets/container 26,460 ft<sup>2</sup>

### INSTALLATION

**Installation**

Glue Down

**Recommended Installation Methods**

Random

### ADHESIVES

For more information on our adhesive options, please visit our website.

See installation instructions for more information on adhesive use.

### WARRANTIES

22 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions

### CERTIFICATIONS


**Declare.**

**M/PACT™**  
CARBON NEUTRAL PROGRAM
