

# LUMENOLOGY

Light Stitch, Light Wash, Reflective - **FLEXFORM™** LVT – 2.5 mm

Made to Order

Luxury Vinyl Tile

## Construction

High Performance Luxury Vinyl Tile

## Finish

ProGuard™ Coating

## Wear Layer Thickness

22 mil (0.55 mm)

## Overall Thickness

2.5 mm (0.098")

## Edge Profile

Square

## Critical Radiant Flux (ASTM E648)

Pass - Class I

## Smoke Density (ASTM E662)

Pass - ≤ 450

## Flexibility (ASTM F137)

Pass

## Heat Stability by Color Change (ASTM F1514)

Pass

## Light Stability (ASTM F1515)

Pass

## Static Coefficient of Friction (ASTM D2047)

Pass

## Dimensional Stability (ASTM F2199)

Pass

## Resistance to Chemicals (ASTM F925)

Pass

## Static Load Limit (ASTM F970)

Pass

## Installation

Glue down

## Tile Size

25 cm x 100 cm (9.84" x 39.37")

## Pieces Per Box

16

## Weight Per Box

37.6 lb (17.06 kg)

## Quantity Per Box

42.9 ft<sup>2</sup> (3.99 m<sup>2</sup>)

## Recommended Installation Method

Ashlar, Random, Herringbone

## Warranty

15 Year Limited Commercial Wear Warranty

## WARRANTIES

15 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions.

## ADHESIVE

For more information on our adhesive options, please visit our website.

See installation instructions for more information on adhesive use.



**Declare.**

