

MESA

RIGIDFORM FREE™ Resilient

Resilient Tile

GENERAL

Construction

PVC-Free Acoustic Rigid Core Tile

Finish

ProGuard MAX™ Coating

Overall /Wear Layer Thickness 4.5 mm/20 mil

Integrated Pad

1.0 mm IXPE pad

Edge Profile

Tongue and Groove

PERFORMANCE

Critical Radiant Flux (ASTM E648)

Pass - Class I

Smoke Density (ASTM E662)

Pass - ≤ 450

Resistance to Heat (ASTM F1514)

Pass

Resistance to Light (ASTM F1515)

Pass

Resistance to Chemicals (ASTM F925)

Pass

Static Coefficient of Friction (ASTM D2047)

Pass

Dynamic Coefficient of Friction (ANSI A137)

Pass

ASTM E492 IIC Rating

55 (6" no drop ceiling)

60 (8" no drop ceiling)

51 (18" OWT with ceiling)

SUSTAINABILITY

Embodied Carbon
8.3 (kg CO₂e)/m²

TILE/PLANK SIZE

Tile/Plank Size

Tierra: 7" x 48"

Mar: 18" x 36"

SHIPPING

Pieces Per Box

7" x 48" planks: 14

18" x 36" tiles: 7

Weight Per Box

7" x 48" planks: 39.82 lb (18.06 kg)

18" x 36" tiles: 38.45 lb (17.44 kg)

Quantity Per Box
7" x 48" planks: 32.67 ft² (3.04 m²)18" x 36" tiles: 31.50 ft² (2.93 m²)
Quantity Per Pallet/Container

7" x 48" planks:

65 cartons/pallet 2,123.35 ft²14 pallets/container 29,726 ft²

18" x 36" planks:

42 cartons/pallet 1,323 ft²20 pallets/container 26,460 ft²

INSTALLATION

Installation

Glue Down

Recommended Installation Methods

Random

ADHESIVES

For more information on our adhesive options, please visit our website.

See installation instructions for more information on adhesive use.

WARRANTIES

22 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions

CERTIFICATIONS


Declare.

M/PACT™
CARBON NEUTRAL PROGRAM
