

# LOCAL MEASURE 2.5

## FLEXFORM™ LVT

Luxury Vinyl Tile

### Construction

High Performance Luxury Vinyl Tile

### Finish

2.5 mm: ProGuard™ Coating

### Wear Layer Thickness

2.5 mm: 22 mil

### Overall Layer Thickness

2.5 mm (0.098")

### Edge Profile

Square

### Critical Radiant Flux (ASTM E648)

Pass - Class I

### Smoke Density (ASTM E662)

Pass - ≤ 450

### Flexibility (ASTM F137)

Pass

### Heat Stability by Color Change (ASTM F1514)

Pass

### Light Stability (ASTM F1515)

Pass

### Static Coefficient of Friction (ASTM D2047) Pass

### WARRANTIES

2.5 mm: 15 Year Commercial

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions.

### Dimensional Stability (ASTM F2199)

Pass

### Resistance to Chemicals (ASTM F925)

Pass

### Static Load Limit (ASTM F970)

Pass

### Installation

Direct Glue

### Nominal Sizes

6" x 48" (15.24 cm x 121.92 cm)

18" x 18" (46.32 cm x 46.32cm)

12" x 24" (31.08 cm x 61.56 cm)

### Pieces Per Box

6" x 48": 18

18" x 18": 16

12" x 24": 18

### Weight Per Box

6" x 48": 31.0 lb (14.06 kg)

18" x 18": 29.5 lb (13.38 kg)

12" x 24": 29.3 lb (13.29 kg)

### Quantity Per Box

6" x 48": 36.0 ft2 (3.34 m2)

18" x 18": 36.0 ft2 (3.34 m2)

12" x 24": 36.0ft2 (3.34 m2)

### Recommended Installation Method

Ashlar, Random, Herringbone

### Warranty

15 Year Limited Commercial Wear Warranty

### ADHESIVE

For more information on our adhesive options, please visit our website. See installation instructions for more information on adhesive use.

