



LOCAL MEASURE 2.5MM LVT

MANUFACTURING LOCATION

USA

PRODUCT ATTRIBUTES

Comfort, acoustics, site related solutions, aesthetics, durability, sustainability, ergonomics, indoor air quality

Embodied Carbon (kg CO2e)/m2	10.2
% Pre-Consumer Recycled Content	21.0%
% Post-Consumer Recycled Content	0.0%

TVOC Range: 0.5 mg/m3 or less

CERTIFICATIONS/LABELS/DECLARATION

CDPH v1.2 - 2017 Compliant: Yes

FloorScore®: [SCS-FS-06186](#)

Indoor Air Quality - Adhesives: [LVT Standard Adhesive](#)

Declare Label: [MKN-0034](#)

LEED CERTIFICATION CREDIT CONTRIBUTION POTENTIAL

LEED BD+C v4, v4.1 - Construction Waste Management

LEED BD+C v4 - Interior Life-Cycle Impact Reduction

LEED BD+C v4.1 - Life Cycle Impact

Product Disclosure, Reporting & Optimization

LEED BD+C v4, v4.1 - Environmental Product Declarations

LEED BD+C v4, v4.1 - Sourcing of Raw Materials

LEED BD+C v4, v4.1 - Material Ingredients

LEED BD+C v4, v4.1 - Low Emitting Materials

LEED BD+C v4 - Certified Multi-Attribute Products and Materials

LEED BD+C v4.1 - Product Certifications

LEED BD+C v4.1 - Design Innovation: Biophilic Design

LEED BD+C v4 - Interior Lighting: Lighting Quality

LEED BD+C v4 - Procurement of Low Carbon Construction Materials (Pilot)

LEED BD+C v4 - Purchasing-Facility Maintenance and Renovation

LEED O+M EB v4, v4.1 - Purchasing-Facility Maintenance and Renovation

WELL BUILDING CERTIFICATION POTENTIAL

Materials X05 - Enhanced Materials Restrictions

Materials X06 - VOC Restrictions

Materials X07 - Material Transparency

Materials X08 - Materials Optimization

Mind M02 - Nature and Place

Mind M07 - Restorative Spaces

It Take Humans to Protect Humanity.

Scan the QR code for more information.

Contact your Rep with Sustainability Questions

Millikenfloors.com | 800.824.2246 |

04/24/25

