Milliken.

FORMWORK

Formwork

Modular Tile

Construction

Tufted, Level Loop

Tile Sizes

50 cm x 50 cm (19.7" x 19.7") 25 cm x 1 m (9.85" x 39.4")

Yarn Type

Universal Fibers® Solution-Dyed Nylon Type 6,6

Stain Repel / Stain Resist / Soil

Release

StainSmart®

Dye Method

Solution Dyed

Tufted Face Weight

 $18 \text{ oz/yd}^2 (610.3 \text{ g/m}^2)$

Gauge

1/10

Stitches Per Inch

11.0

Tufts

110/in² (1,704/100 cm²)

Finished Pile Height

0.15" (3.81 mm)

Finished Pile Thickness

0.10" (2.54 mm)

Average Density (Finished)

6,300

Standard Backing

PVC-Free WellBAC[™] Comfort Cushion Available with TractionBack®

Available with Hactionback

Recycled Content by Total Weight Standard Backing: 41.6% Pre-

Consumer, 0.0% Post-Consumer NSF 140 Platinum Backing Option: 31.1% Pre-Consumer, 10.5% Post-

Consumer

Nominal Total Thickness

0.34" (8.6 mm)

Nominal Total Weight

 $102.0 \text{ oz/yd}^2 (3,458 \text{ g/m}^2)$

Flammability (Radiant Panel

ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or

ASTM-E-662)

 ≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20%

R.H.,70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating

Severe Traffic End-Use Applications

Recommended Maintenance

MilliCare® Textile and Carpet Care

Service Network

Indoor Air Quality—CRI Green Label

PlusTM

GLP7205, Carpet Category 13X

Recommended Installation Method(s)

Monolithic, Planks

WARRANTIES

Lifetime Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency
Lifetime Floor Release

Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Staining/Soiling (StainSmart®)
Lifetime Dimensional Stability

Lifetime Tuft Bind Lifetime Edge Ravel Flammability











This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.