

OBEX™ GRID: VINYL

11mm Closed

Entrance Flooring

MODULAR GRID

Grid Material

100% UV-Resistant PVC

Grid Size

Nominal: 7.87" x 7.87" (200 mm x 200 mm)

Installed Usable: 7.80" x 7.80" (198 mm x 198 mm)

Total Nominal Thickness

11 mm (0.43")

Grid Color

Black

Temperature Resistance

-22°F to +122°F (-30°C to +50°C)

Nominal Total Weight

23.8 oz/ft² (7,275 g/m²)

Flammability (Radiant Panel ASTM-E-648)

≥ 0.45 (Class I)

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)

Self-Extinguishing

Recommended Maintenance

Daily Vacuum, Deep Clean via Hot Water Extraction

Rolling Load (ASTM F2753)

No noticeable deformation or damage to the structural integrity with a 400 pound per wheel at 2,500 cycles with load applied to a 200 mm diameter, 32 mm wide rubber tread castor.

Grids Per Box

30 Pieces, 12.66 ft² (1.18 m²)

Installation Zone Application

Zone 1 or Zone 2

ADA / BS8300 / ISO 21542 Compliant

WARRANTIES

1 Year Manufacturing Defect Warranty

5 Year Wear Warranty



Find us in

MasterSpec®

Powered by Deltek Specpoint®