

# CHANGE AGENT LVT

## Conjure, Relic, Rootwork – FLEXFORM™ LVT

Luxury Vinyl Tile

**Construction**

High Performance Luxury Vinyl Tile

**Finish**

ProGuard MAX™ Coating

**Wear Layer Thickness**

22 mil (0.55 mm)

**Overall Layer Thickness**

5.0 mm (0.197")

**Edge Profile**

Micro Bevel

**Critical Radiant Flux (ASTM E648)**

Pass - Class I

**Smoke Density (ASTM E662)**

Pass - ≤ 450

**Flexibility (ASTM F137)**

Pass

**Heat Stability by Color Change (ASTM F1514)**

Pass

**Light Stability (ASTM F1515)**

Pass

**Static Coefficient of Friction (ASTM D2047)**

Pass

**Dimensional Stability (ASTM F2199)**

Pass

**WARRANTIES**

22 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions.

**Declare.**ORTHO-PHTHALATE  
FREE**M/PACT™**  
CARBON NEUTRAL PROGRAM**Resistance to Chemicals (ASTM F925)**

Pass

**Static Load Limit (ASTM F970)**

Pass

**Installation**

Direct Glue

**Tile Size***Conjure and Rootwork:* 25 cm x 150 cm (9.84" x 59.1")*Relic:* 25 cm x 100 cm (9.84" x 39.4")**Pieces Per Box***Conjure:* 6*Relic:* 10*Rootwork:* 6**Weight Per Box***Conjure:* 49.8 lb (22.6 kg)*Relic:* 55.3 lb (25.1 kg)*Rootwork:* 49.8 lb (22.6 kg)**Quantity Per Box***Conjure:* 24.22 ft<sup>2</sup> (2.25 m<sup>2</sup>)*Relic:* 26.91 ft<sup>2</sup> (2.5 m<sup>2</sup>)*Rootwork:* 24.22 ft<sup>2</sup> (2.3 m<sup>2</sup>)**Recommended Installation Method**

Ashlar, Random, Herringbone

**Warranty**

22 Year Limited Commercial Wear Warranty

**ADHESIVE**

For more information on our adhesive options, please visit our website.

See installation instructions for more information on adhesive use.