

# R | Local Reserve

## PRODUCT SPECIFICATIONS



<b>COLLECTION</b>	Local Reserve
<b>STYLE NUMBER</b>	I592V
<b>CONSTRUCTION</b>	Multilayer SPC
<b>WEAR LAYER THICKNESS</b>	20 mil / 0.02 inches (0.508 mm)
<b>OVERALL THICKNESS</b>	0.157 inches (4 mm)
<b>EDGE PROFILE</b>	Micro-Bevel
<b>REFERENCE SPECIFICATION</b>	ASTM F3261
<b>FINISH</b>	ExoGuard+®
<b>INSTALLATION TYPE</b>	InLine Level Edge
<b>INSTALLATION</b>	Glue Down
<b>RECOMMENDED ADHESIVE</b>	4200 (4 gal), 2200 (4 gal) or 4252 (4 gal)

## Packaging

**PLANK SIZE**  
**AREA /BOX**  
**WEIGHT /BOX**

### US Units

7 inches W x 48 inches L  
27.96 sq ft  
42.24 lbs

### Metric Units

17.8 cm W x 121.9 cm L  
2.6 sq m  
19.2 kg

## Performance Testing

**STATIC LOAD / ASTM F970**

Passes (Modified), \*2500 lbs

**RESIDUAL INDENTATION / ASTM F1914**

Passes

**RESISTANCE TO CHEMICALS / ASTM F925**

Passes

**RADIANT PANEL / ASTM E648**

Passes, Class I

**COEFFICIENT OF FRICTION (ASTM D2047, SLIP RESISTANCE)**

≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

\*Results are based on a laboratory test and used for comparative purposes. Real life load limit may vary.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranty


15 Year Commercial Limited.

Commercial Limited Underbed Bond Shaw Lockworx+ Resilient, Shaw 4151.

Please visit [patcraft.com](https://patcraft.com) for the most current warranty information.

# R | Local Reserve

## Installation Methods



Brick

Stagger

[Installation Guidelines](#)

[Maintenance Guidelines](#)

## Environmental Specifications

**EMBODIED CARBON (CRADLE TO GATE)**

12.1 kg CO<sub>2</sub>/m<sup>2</sup>

## Materials

**RECYCLED CONTENT**

Pre-consumer - 20%

## Third Party Certifications

**HEALTH PRODUCT DECLARATION (HPD)**

[1000 ppm Disclosure](#)

**ENVIRONMENTAL PRODUCT DECLARATION (EPD)**

[3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017](#)

**ENVIRONMENTAL GUARANTEE**

The products in this collection are In The Loop – they are fully recyclable through our re[TURN]® Reclamation Program. We will facilitate the pick-up and free return of a minimum of 100 SY of EcoWorx®, 500 SY of ReWorx™ products or 5,000 SF of Shaw-manufactured resilient products to be recycled. Participating in re[TURN]® lowers carbon emissions of these products by reducing virgin materials needed for making new products.

[Certified](#)

**FLOORSCORE®**

## Available Colorways



CASHEW-V2 00105  
V2 - SLIGHT VARIATION



TALC-V2 00500  
V2 - SLIGHT VARIATION



CHICKAREE-V3 00525  
V3 - MODERATE  
VARIATION



FOG-V2 00560  
V2 - SLIGHT VARIATION



IRON-V2 00580  
V2 - SLIGHT VARIATION



SEDONA-V2 00750  
V2 - SLIGHT VARIATION

# R | Local Reserve



STAG-V3 00760  
V3 - MODERATE  
VARIATION



OAT-V2 01031  
V2 - SLIGHT VARIATION



DERBY-V2 01036  
V2 - SLIGHT VARIATION



JUTE-V3 02001  
V3 - MODERATE  
VARIATION



DOVE-V2 05110  
V2 - SLIGHT VARIATION



CINDER-V2 05113  
V2 - SLIGHT VARIATION



LATTE-V4 07059  
V4 - SUBSTANTIAL  
VARIATION



TRUFFLE-V3 07060  
V3 - MODERATE  
VARIATION



CAROB-V2 07067  
V2 - SLIGHT VARIATION



MOCHA-V2 07210  
V2 - SLIGHT VARIATION



HAZELNUT-V2 07212  
V2 - SLIGHT VARIATION



REED-V2 07213  
V2 - SLIGHT VARIATION

## Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

