

R | Local Reserve

PRODUCT SPECIFICATIONS



COLLECTION	Local Reserve
STYLE NUMBER	I592V
CONSTRUCTION	Multilayer SPC
WEAR LAYER THICKNESS	20 mil / 0.02 inches (0.508 mm)
OVERALL THICKNESS	0.157 inches (4 mm)
EDGE PROFILE	Micro-Bevel
REFERENCE SPECIFICATION	ASTM F3261
FINISH	ExoGuard+®
INSTALLATION TYPE	InLine Level Edge
INSTALLATION	Glue Down
RECOMMENDED ADHESIVE	4200 (4 gal), 2200 (4 gal) or 4252 (4 gal)

Packaging

PLANK SIZE
AREA /BOX
WEIGHT /BOX

US Units

7 inches W x 48 inches L
 27.96 sq ft
 42.24 lbs

Metric Units

17.8 cm W x 121.9 cm L
 2.6 sq m
 19.2 kg

Performance Testing

STATIC LOAD / ASTM F970

Passes (Modified), *2500 lbs

RESIDUAL INDENTATION / ASTM F1914

Passes

RESISTANCE TO CHEMICALS / ASTM F925

Passes

RADIANT PANEL / ASTM E648

Passes, Class I

COEFFICIENT OF FRICTION (ASTM D2047, SLIP RESISTANCE)

≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

*Results are based on a laboratory test and used for comparative purposes. Real life load limit may vary.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranty


15 Year Commercial Limited.

Commercial Limited Underbed Bond Shaw Lockworx+ Resilient, Shaw 4151.

Please visit patcraft.com for the most current warranty information.

R | Local Reserve

Installation Methods



Brick

Stagger

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Environmental Specifications

EMBODIED CARBON (CRADLE TO GATE)

12.1 kg CO₂/m²

Materials

RECYCLED CONTENT

Pre-consumer - 20%

Third Party Certifications

HEALTH PRODUCT DECLARATION (HPD)

[1000 ppm Disclosure](#)

ENVIRONMENTAL PRODUCT DECLARATION (EPD)

[3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017](#)

ENVIRONMENTAL GUARANTEE

The products in this collection are In The Loop – they are fully recyclable through our re[TURN]® Reclamation Program. We will facilitate the pick-up and free return of a minimum of 100 SY of EcoWorx®, 500 SY of ReWorx™ products or 5,000 SF of Shaw-manufactured resilient products to be recycled. Participating in re[TURN]® lowers carbon emissions of these products by reducing virgin materials needed for making new products.

[Certified](#)

FLOORSCORE®

Available Colorways



CASHEW-V2 00105
V2 - SLIGHT VARIATION



TALC-V2 00500
V2 - SLIGHT VARIATION



CHICKAREE-V3 00525
V3 - MODERATE
VARIATION



FOG-V2 00560
V2 - SLIGHT VARIATION



IRON-V2 00580
V2 - SLIGHT VARIATION



SEDONA-V2 00750
V2 - SLIGHT VARIATION

R | Local Reserve



STAG-V3 00760
V3 - MODERATE
VARIATION



OAT-V2 01031
V2 - SLIGHT VARIATION



DERBY-V2 01036
V2 - SLIGHT VARIATION



JUTE-V3 02001
V3 - MODERATE
VARIATION



DOVE-V2 05110
V2 - SLIGHT VARIATION



CINDER-V2 05113
V2 - SLIGHT VARIATION



LATTE-V4 07059
V4 - SUBSTANTIAL
VARIATION



TRUFFLE-V3 07060
V3 - MODERATE
VARIATION



CAROB-V2 07067
V2 - SLIGHT VARIATION



MOCHA-V2 07210
V2 - SLIGHT VARIATION



HAZELNUT-V2 07212
V2 - SLIGHT VARIATION



REED-V2 07213
V2 - SLIGHT VARIATION

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

