

## R | Natural State 12 Click

## PRODUCT SPECIFICATIONS



<b>COLLECTION</b>	Natural State
<b>STYLE NUMBER</b>	1531V
<b>CONSTRUCTION</b>	Multilayer SPC with Acoustic Backing
<b>WEAR LAYER</b>	
<b>THICKNESS</b>	12 mil / 0.012 inches (0.305 mm)
<b>OVERALL THICKNESS</b>	0.173 inches (4.4 mm)
<b>EDGE PROFILE</b>	Micro-Bevel
<b>REFERENCE SPECIFICATION</b>	ASTM F3261
<b>FINISH</b>	ExoGuard®
<b>INSTALLATION TYPE</b>	Click
<b>INSTALLATION</b>	Floating

## Packaging

## PLANK SIZE

## US Units

## Metric Units

6.92 inches W x 48.03 inches L

17.6 cm W x 122 cm L

## PIECES / BOX

12

## AREA / BOX

27.73 sq ft

2.6 sq m

## WEIGHT / BOX

41.32 lbs

18.7 kg

## Performance Testing

## STATIC LOAD / ASTM F970

Passes

## RESIDUAL INDENTATION / ASTM F1914

Passes

## RADIANT PANEL / ASTM E648

Passes, Class I

## SMOKE DENSITY / ASTM E662

Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.


## Warranty

10 Year Commercial Limited Warranty.

Please visit [patcraft.com](http://patcraft.com) for the most current warranty information.

# R | Natural State 12 Click

## Installation Methods



Stagger

[Installation Guidelines](#)

[Maintenance Guidelines](#)

## Environmental Specifications

**EMBODIED CARBON (CRADLE TO GATE)**

20.5 kg CO<sub>2</sub>/m<sup>2</sup>

## Third Party Certifications

**HEALTH PRODUCT DECLARATION (HPD)**

[1000 ppm Disclosure](#)

**ENVIRONMENTAL PRODUCT DECLARATION (EPD)**

[3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017](#)

**FLOORSCORE®**

[Certified](#)

## Available Colorways



DRIFTWOOD-V2 00100



HONEY WALNUT-V2 00130



BASSWOOD-V2 00170



QUARRY-V2 00500



PEWTER-V3 00520




ASHWOOD-V3 00540



VINTAGE OAK-V2 00700



SPRINGWOOD-V2 00710



SABLE-V2 00720



HERITAGE BROWN-V3 00730



UMBER-V2 00740



SPICED CHESTNUT-V2 00750