patcraft®

Timber Grove II SPC PRODUCT SPECIFICATIONS

COLLECTION	Timber Grove II
STYLE NUMBER	I599V
CONSTRUCTION	Multilayer SPC
WEAR LAYER THICKNESS	20 mil / 0.02 inches (0.508 mm)
OVERALL THICKNESS	0.157 inches (4 mm)
EDGE PROFILE	Micro-Bevel
REFERENCE SPECIFICATION	ASTM F3261
FINISH	ExoGuard+®
INSTALLATION TYPE	InLine Level Edge
INSTALLATION	Glue Down
RECOMMENDED ADHESIVE	4200 (4 gal), 2200 (4 gal) or 4252 (4 gal)

Packaging

	US Units	Metric Units
PLANK SIZE	7 inches W x 48 inches L	17.8 cm W x 121.9 cm L
AREA /BOX	27.96 sq ft	2.6 sq m
WEIGHT /BOX	42.24 lbs	19.2 kg

Performance Testing

STATIC LOAD / ASTM F970	Passes (Modified), *2500 lbs
RESIDUAL INDENTATION / ASTM F1914	Passes
RESISTANCE TO CHEMICALS / ASTM F925	Passes
RADIANT PANEL / ASTM E648	Passes, Class I
COEFFICIENT OF FRICTION (ASTM D2047, SLIP RESISTANCE)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

*Results are based on a laboratory test and used for comparative purposes. Real life load limit may vary.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranty

15 Year Commercial Limited.

Commercial Limited Underbed Bond Shaw Lockworx+ Resilient, Shaw 4151.

Please visit patcraft.com for the most current warranty information.

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company

TRANSFORMSPACE

For reference purposes only if printed or downloaded.

patcraft®

R | Timber Grove II SPC

Installation Methods



Brick



Stagger

Installation Guidelines

Maintenance Guidelines

Environmental Specifications

EMBODIED CARBON (CRADLE TO GATE)	12.1 kg CO_2/m^2

Materials

RECYCLED CONTENT	Pre-consumer - 20%

Third Party Certifications

HEALTH PRODUCT DECLARATION (HPD)	1000 ppm Disclosure
ENVIRONMENTAL PRODUCT DECLARATION (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
ENVIRONMENTAL GUARANTEE	The products in this collection are In The Loop – they are fully recyclable through our re[TURN]® Reclamation Program. We will facilitate the pick-up and free return of a minimum of 100 SY of EcoWorx®, 500 SY of ReWorx™ products or 5,000 SF of Shaw-manufactured resilient products to be recycled. Participating in re[TURN]® lowers carbon emissions of these products by reducing virgin materials needed for making new products.
FLOORSCORE®	Certified

Available Colorways

ASTER-V4 00170
V3 - MODERATE VARIATION

SPROUT-V2 00173
V2 - SLIGHT VARIATION

HEATHER-V3 00174
V3 - MODERATE VARIATION

MERIGOLD-V2 00230
V2 - SLIGHT VARIATION

CACTUS-V2 00350
V2 - SLIGHT VARIATION



ARBOR-V2 00360
V2 - SLIGHT VARIATION

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company

TRANSFORMSPACE

For reference purposes only if printed or downloaded.

patcraft®

R | Timber Grove II SPC

TURQUOISE-V2 00370
V2 - SLIGHT VARIATION

CARIBE-V2 00400
V2 - SLIGHT VARIATION

INDIGO-V2 00450
V2 - SLIGHT VARIATION

SILVER-V2 00540
V2 - SLIGHT VARIATION

JUNIPER-V2 00559
V2 - SLIGHT VARIATION

HEDGEROW-V2 00564
V2 - SLIGHT VARIATION

MOORELAND-V2 00568
V4 - SUBSTANTIAL VARIATION

HEMLOCK-V2 00572
V2 - SLIGHT VARIATION


ONYX-V2 00580
V2 - SLIGHT VARIATION

MANDARIN-V2 00600
V2 - SLIGHT VARIATION

CORAL-V2 00650
V2 - SLIGHT VARIATION

LAUREL-V2 00684
V2 - SLIGHT VARIATION

BISTRE-V2 00710
V2 - SLIGHT VARIATION

FRONTIER-V2 00774
V2 - SLIGHT VARIATION

BOXWOOD-V2 00775
V2 - SLIGHT VARIATION

GARNET-V2 00850
V2 - SLIGHT VARIATION

SHADY GROVE-V3 05012
V3 - MODERATE VARIATION

YARROW-V2 05013
V2 - SLIGHT VARIATION

INKBERRY-V3 05016
V3 - MODERATE VARIATION

PAVILLION-V4 05019
V4 - SUBSTANTIAL VARIATION

PERGOLA-V3 07003
V2 - SLIGHT VARIATION

TOPIARY-V3 07004
V3 - MODERATE VARIATION

COURTYARD-V3 07005
V2 - SLIGHT VARIATION

TRELLIS-V3 07007
V3 - MODERATE VARIATION

LATTICE-V2 07008
V2 - SLIGHT VARIATION

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company

TRANSFORMSPACE

For reference purposes only if printed or downloaded.

patcraft®

R | Timber Grove II SPC

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1
Uniform Appearance

V2
Slight Variation

V3
Moderate Variation

V4
Substantial Variation

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company

TRANSFORMSPACE

For reference purposes only if printed or downloaded.