



M | Revive product specifications



COLLECTION Renewed Escape STYLE NUMBER 10612 PRODUCT TYPE Tile CONSTRUCTION Multi-Level Pattern Loop FIBER TYPE EcoSolution Q® Nylon DYE METHOD 100% Solution Dyed **PRIMARY BACKING** Non-Woven Synthetic SECONDARY BACKING StrataWorx® Tile

Metric Units PRODUCT SIZE 24 inches x 24 inches 60.96 cm x 60.96 cm AREA PER BOX 80 ft² 7.43 m^2 PIECES PER BOX 20 **GAUGE** 1/10 inches 39.37 per 10 cm STITCHES 10.17 per inches 40.03 per 10 cm FINISHED PILE THICKNESS 0.086 inches 2.18 mm **AVERAGE DENSITY** 6279 oz/yd3 0.23 g/cm³ KILOTEX 8.89 TOTAL THICKNESS 0.209 inches 5.31 mm TUFTED YARN WEIGHT 15 oz/yd^2 508.59 g/m²

Performance Testing

PILL TEST Pass
RADIANT PANEL Class I

NBS SMOKELess than 450ELECTROSTATIC PROPENSITYLess than 3.5 kv

CRI GREENLABEL PLUS GLP2671

ADA COMPLIANCE >0.6, meets the recommended static coefficient of friction

for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranty

15 Year Commercial Limited Warranty

Please visit patcraft.com for the most current warranty information.

TRANS**FORM SPACE**





M Revive

Installation Methods











Quarter Turn Random

Monolithic

Brick

Ashlar

Installation Guidelines Maintenance Guidelines

Environmental Specifications

RECYCLABILITY 100% recyclable **EMBODIED CARBON (CRADLE TO GATE)** 7.22 Kg CO₂/M²

Materials

Ingredients

DOES NOT CONTAIN does not contain PVC, phthalates or PBD/PBDE

Recycled Content

TOTAL RECYCLED CONTENT (BY WEIGHT) 24% PRE-CONSUMER 24% **POST-CONSUMER** 0% **COUNTRY OF ORIGIN (MANUFACTURER)** USA

Meets or exceeds all local and national regulations in country of manufacture. Manufactured in an ISO9001 & ISO14001 certified facility or equivalent. Recycled content is calculated using system allocation, mass balance, and direct insertion. The actual recycled content in this product will likely vary. For more information email info@patcraft.com.

Third Party Certifications

CRADLE TO CRADLE CERTIFIED® Silver Level (Version 3.1) **HEALTH PRODUCT DECLARATION (HPD)** 1,000 ppm Disclosure

ENVIRONMENTAL PRODUCT DECLARATION 3rd Party Certified in Accordance with ISO14044, ISO14025 &

(EPD) EN15804 **NSF 140** Gold CRI GREEN LABEL PLUS (GLP) **GLP9968 USGBC LEED** contributes



Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice. This carpet is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another carpet design is also strictly prohibited. Visit patcraft.com/testing for more information.





M | Revive

Available Colorways













REFERENCE 00570 VANTAGE 00700