



## GENERAL DESCRIPTION

PPG ProLuxe Premium Deck Cleaner is a unique, premium quality product for restoring the clean, refreshed look to exterior wood and other surfaces. It cleans stains caused by mildew, dirt, algae and mold without scrubbing. Unlike bleach alone, PPG ProLuxe Premium Deck Cleaner works on the surface to lift dirt that can then be rinsed away. This product contains no phosphates, acids, solvents or petroleum distillates. Can be used on decks, wood siding, shakes, shingles, and fences.

## RECOMMENDED SUBSTRATES

Wood

## FEATURES / BENEFITS

- Ready to use - No mixing
- Recommended to use with PPG ProLuxe wood finishes
- Removes dirt, mold & mildew stains

## PRODUCT INFORMATION

SIK100 Deck Cleaner

Ready to use - No mixing

## PACKAGING

1-Gallon (3.78 L)

## PRODUCT DATA

**PRODUCT TYPE:** Water/Sodium Hypochlorite  
**WEIGHT/GALLON:** 8.8 lbs. (4.0 kg) +/- 0.2 lbs. (91 g)

**COVERAGE:** One gallon (3.78 liters) will clean approximately 250 to 300 sq. ft. (23 to 28 square meters). Coverage will vary depending on type, age, and texture of wood.

**CLEANUP:** Rinse tools and spray equipment thoroughly with water.

**STORAGE AND DISPOSAL:** Store in a cool, dry location, in a tightly closed, plastic container. Avoid exposure to sunlight. Do not reuse container. Rinse container thoroughly before disposal. KEEP IN AN UPRIGHT POSITION.

**FLASH POINT:** Over 200°F (93°C)

## LIMITATIONS OF USE

Use of this product may return the original green color to pressure-treated wood.

Application of this product may cause a fuzzy appearance to wood previously damaged by pressure washing or excessive weathering.

Application to new wood or newly sealed wood may cause spotting and discoloration.

May cause redwood to darken.

Do not allow to come into contact with metal, fabric, floor coverings, or lawn furniture.

KEEP IN AN UPRIGHT POSITION. PROTECT FROM FREEZING.

## APPLICATION INFORMATION

**SAFETY PRECAUTIONS:** Wear chemical-resistant gloves, safety goggles, and protective clothing. Do not mix with any other chemicals or other household cleaning products as hazardous fumes may result. Surfaces are slippery when wet. Use caution when walking on wet surfaces during application. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our web site or by calling 1-800-441-9695.

**PRETEST:** Always test a small hidden area, rinse and let dry before applying this product.

**AREA PREPARATION:** Spray all plants and vegetation liberally with water before and after application. Cover delicate vegetation to avoid damage.

**APPLICATION:** Surfaces to be cleaned must be thoroughly dry. Cleaner should be applied at full strength with spray equipment recommended below. When treating vertical surfaces, apply from bottom to top. Spray the affected area liberally and allow to stand for 5 to 10 minutes. NO SCRUBBING NECESSARY. Cleaning action will occur within minutes. Thoroughly rinse treated surface and surrounding areas with large amounts of water to neutralize cleansing action. A second application may be conducted if necessary.

**FOR PERIODIC CLEANING OF COMPOSITE DECKING:** Apply cleaner liberally and work into surface with a stiff broom (slight foaming should be seen, if not, apply more cleaner). Rinse, let dry, and apply a second time if needed. Slight yellowing of the deck is normal and will fade in a matter of days.

**RECOMMENDED SPRAY EQUIPMENT:** Use a plastic, pump-style garden sprayer and hose.

**THINNING:** Do not thin. Do not mix with any other chemicals or other household cleaning products as hazardous fumes may result.

**Permissible temperatures during application:**

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C
Substrate:	50 to 90°F	10 to 32°C

## PRECAUTIONS

**DANGER! CAUSES EYE AND SKIN BURNS. CAUSES RESPIRATORY TRACT IRRITATION.** Do not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. Call physician immediately. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.). For more ingredient information, visit [www.ppgpaints.com](http://www.ppgpaints.com) or call (412) 492-5555.

© 2022 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. ProLuxe is a registered trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Architectural Finishes, Inc.  
One PPG Place  
Pittsburgh, PA 15272  
[www.ppgpaints.com](http://www.ppgpaints.com)  
[www.perfectwoodstains.com](http://www.perfectwoodstains.com)

Technical Services  
1-800-441-9695

Architect/Specifier  
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.  
1550 rue Ampère, Suite 500  
Boucherville (Quebec) J4B 7L4

SIK100 12/2022