

PHYSICAL PROPERTIES:

Width:	55/56"	Finished Width:	54"
Weight:	Type II, 20 oz/Lin. Yd. 626 Grams per Lin. Meter	Backing:	Polycotton Osnaburg
Tear Strength:	25 x 25	Tensile Strength:	50 x 55
Repeat:	Random Match / Reverse Hang		
Fire Rated:	Class A / ASTM E-84-91A Tunnel Test NFPA Life Safety Code 101-6-5.3		

Flame Spread - 15* Smoke Developed - 20*

This test method is also published under the following designations:
ANSI 2.5 NFPA 255 UBC 42-1 UL 723

*The numerical flame spread rating referenced herein is not intended to reflect hazards presented by this or any other material under actual fire conditions. Arc-Com shall submit, upon request, a Certificate of Compliance that wallcoverings used meet specifications and modifications outlined herein.

MEA	
Acceptance:	Approved for use in the City of New York, Department of Buildings.
Federal	
Specifications:	Meets or exceeds requirements for Type II material for Federal Specifications CCC-W-408 A/C/D and CFFA-W-101-C. Tested in accordance with test procedures detailed in Federal Specification CCC-T-191A.

PERFORMANCE FEATURES:

Composition:	Free of Cadmium, Mercury and ozone-depleting chemicals.
Permeability:	Vinyl wallcovering has little or no moisture permeability. If the design, construction or maintenance of a building and / or other circumstances allow moisture to accumulate in a wall or wall cavity, vinyl wallcovering can act as a vapor barrier restricting the escape of moisture and increasing the risk of mold growth. Mold and mildew are naturally occurring and are present everywhere in nature. They need only water and organic material (such as wood, paper or plant material) to feed upon and grow. Vinyl wallcovering permeability can be increased through perforation and alternative product constructions with varying degrees of increased permeability depending on methods used. No wallsurfacing material will prevent mold growth if moisture accumulation is permitted to occur. An experienced professional who is familiar with building conditions and circumstances should be consulted concerning benefits and limitations of vinyl wallcovering. Arc-Com Wallcoverings contain additives to resist mold and other micro-biological growth on the product. Those additives, however, will not prevent mold growth if moisture is allowed to accumulate behind the wall. For more information on wallcovering permeability and mold, Arc-Com recommends that you visit www.wallcoverings.org .

Warranty:	5 Year Limited Warranty on Manufacturing Defects.
Installation:	Detailed Arc-Com installation instructions are enclosed with each bolt.

To order a sample, to check stock / delivery, or to place an order, please call Arc-Com Headquarters or one of the Showrooms listed.

Copyright © 2007 Arc-Com Fabrics, Inc. All Rights Reserved.

Showrooms:
Atlanta · Boston · Chicago · Dallas · Houston · Los Angeles · New York City
San Francisco · Washington, DC

International:
Australia · British Columbia · Calgary · Hong Kong · Mexico · Montréal · Taiwan · Toronto

Arc-Com Fabrics, Inc.
33 Ramland South, Orangeburg, NY 10962
1 800 223-5466 www.arc-com.com