








Model: AIRSLATE METAL  
Codes: 100242668  
Group: G-238  
Format: 98 109/256"X47 31/128"X5/64"-5/32" approx.  
Thickness range: "-5/32" approx.



RECOMMENDATIONS		
Recommended adhesive	100217753 POLITECH PREMIUM COMPUESTO A + B 10KG	
Recommended joint	100236449 COLORSTUK RAPID CEMENTO N 5KG	
Recommended joint (wet area)	100120620 S-107 N CEMENTO 0,3L	
Recommended adhesive (wet area)	-	

LABORATORY TESTS		
Bulk density	1450 Kg/m3	UNE EN 1936:2007*
Water absorption at atmospheric pressure	1.00%	UNE-EN 13755:2008*
Flammability	C-S2, d0	UNE-EN 13501-1:2007+A1:2010*
Frost resistance	93.1 MPa	UNE-EN 12371:2010*
Resistance to thermal shock	T2	UNE -EN 16140:2011*
Flame-spread or surface characteristics	CLASE II	ASTM E 84*
Coefficient of linear thermal expansion	23 1/(10E6*K)	UNE-EN 10545-8*
Flexural strength	102.2 MPA	EN 12372*

FEATURES	
 Protection that reduces the appearance of the most common domestic bacteria.	 There are considerable color changes between pieces.
 Material from an Asian country.	 Material suitable for use on indoor walls.
 Gloss-free	 Material suitable for use on shower walls.
 Material that stands out for having an asymmetrical surface.	

PACKING		
Sales units per box	161.46 SQF/CS	
Sales units per pallet	4036.47 SQF/PAL	
Sales units per unit	32.29 SQF/ST	
Sale unit	M2	
Base unit	ST	
Net weight	107.1 LB/SQF	
Gross weight	110.27 LB/SQF	

