
L'ANTIC COLONIAL

Model: METROPOLITAN MOSS

Codes: 100336778 Group: G-226

Format: 7 7/8"X7 7/8"X43/128" approx.



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100236834 COLORSTUK RAPID GRIS N 5KG	
Recommended joint (wet area)	100236834 COLORSTUK RAPID GRIS N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

FEATURES



Material with surface with the ability to produce reflections.



Material suitable for use on shower walls.



Material suitable for use on indoor walls.



No changes in color between pieces.



Material recommended for installation on walls.

DIMENSIONAL FEATURES					
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*			
Side straightness deviation	±0.3 %	UNE-EN ISO 10545-2*			
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*			
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*			

PHYSICAL PROPERTIES				
Water absorption	BIII	ISO 10545-2*		
Breaking strength	>202.41 LBF	>135LBF*		
Crack resistance	PASS	ISO 10545-11*		
Flammability	A1	EN 13501-1*		
Flexural strength	>20 MPA	ISO 10545-4*		

	PACKING	
Sales units per box	9.47 SQF/CS	
Sales units per pallet	568.33 SQF/PAL	
Sales units per unit	0.43 SQF/ST	
Sale unit	M2	
Base unit	ST	
Net weight	358.92 LB/SQF	
Gross weight	371.38 LB/SQF	





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

100336778

METROPOLITAN MOSS

L'ANTIC COLONIAL

CHEMICAL PROPERTIES			
Stain resistance	Clase 5	ISO 10545-14*	
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*	



