

Model: PARMA Limestone

Codes: 100321930

Group: G-226

Format: 3 19/128"X11 13/16"X43/128" approx.



RECOMMENDATIONS

Recommended adhesive	100043280 TIXOCEM PLUS 25KG
Recommended joint	100236419 COLORSTUK 0-4 BEIGE N 5KG
Recommended joint (wet area)	100236808 COLORSTUK RAPID BEIGE N 5KG
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG

DIMENSIONAL FEATURES

Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.3 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

FEATURES



Gloss-free



Material suitable for use on shower walls.



Material suitable for use on indoor walls.



There are consistent color changes between pieces.



Material recommended for installation on walls.

PHYSICAL PROPERTIES

Water absorption	BIII	ISO 10545-2*
Breaking strength	>202.41 LBF	>135LBF*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1	EN 13501-1*
Flexural strength	>20 MPA	ISO 10545-4*

CHEMICAL PROPERTIES

Stain resistance	Clase 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*



PACKING

Sales units per box	7.23 SQF/CS	
Sales units per pallet	723.33 SQF/PAL	
Sales units per unit	0.26 SQF/ST	
Sale unit	M2	
Base unit	ST	
Net weight	336.18 LB/SQF	
Gross weight	345.08 LB/SQF	

