

Model: PIGMENTS HONEY

Codes: 100371125

Group: G-226

Format: 5 101/128"X5 101/128"X43/128" approx.



RECOMMENDATIONS

Recommended adhesive	100201526 ONE-FLEX PREMIUM BLANCO 25KG
Recommended joint	100236794 COLORSTUK RAPID MARFIL N 5KG
Recommended joint (wet area)	100236794 COLORSTUK RAPID MARFIL N 5KG
Recommended adhesive (wet area)	100201526 ONE-FLEX PREMIUM BLANCO 25KG

DIMENSIONAL FEATURES

Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

FEATURES

-  Gloss-free
-  Material suitable for use on shower walls.
-  Material suitable for use on outdoor walls.
-  Material suitable for use on indoor walls.
-  Material suitable for use on indoor floors.
-  There are slight color changes between pieces.
-  Material recommended for installation on the floor.

PHYSICAL PROPERTIES

Water absorption	Bla	ISO 10545-3*
Breaking strength	>472.29 LBF	>292LBF*
Resistance to thermal shock	PASS	ISO 10545-9*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1f I/A1	EN 13501-1*
Flexural strength	>51 N/mm2	ISO 10545-4*
Slip resistance (wet pendulum) trrl	CLASE 1	UNE EN 16165*
Dynamic coefficient of friction (dcof)	≥ 0,42	
Abrasion resistance	PEI 3	ISO 10545-7*

CHEMICAL PROPERTIES

Stain resistance	CL 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*



PACKING

Sales units per box	3.26 SQF/CS	
Sales units per pallet	586.15 SQF/PAL	
Sales units per unit	0.23 SQF/ST	
Sale unit	M2	
Base unit	ST	
Net weight	474.41 LB/SQF	
Gross weight	490.88 LB/SQF	

