

Specifications  
Silent Rhythm  
399539

**maharam**

**Application**

Walls

**Characteristics**

Content: 65% Cellulose, 35% Latex  
Finish: PFAS-Free Protective Topcoat  
Backing: None  
Reference Dimension: 10' H x 20' W (305cm x 610cm)  
Traffic: Moderate Traffic  
Customs: Scalable  
Country of Origin: USA  
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.  
Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](https://maharam.com).

**Price**

Contact your sales representative for pricing.

**Maintenance**

W-Clean with water-based cleanser.



**Testing**

Flammability: AS/NZS 3837 Adhered  
ASTM E84 Adhered  
CAN ULC S102 Adhered  
ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications  
Silent Rhythm  
399539

**maharam**

**Environmental**


Greenguard Gold Certified  
LBC Red List Free  
Contains Bio-Based Content  
FR Free  
Free of Intentionally Added PFAS

**Warranty**

3 years.

© 2011 Jacob Hashimoto, Maharam under license

Complete product information at [maharam.com](http://maharam.com)  
800.645.3943



001