

Specifications  
Tek-Wall Lucent  
300066

**maharam**

**Application**

Upholstered Walls, Walls

**Characteristics**

Content: 60% Polyester, 40% Post-Consumer Recycled Polyester

Finish: Stain Repellent

Backing: Acrylic

Width: 57" (145cm)

Bolt Size: 30 yards (27 m)

Weight: 16.7 oz/ly (500 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

**Price**

Contact your sales representative for pricing.

**Maintenance**

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.



**Testing**

Acoustics: ASTM C423, 0.85 NRC

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

ASTM E84 Unadhered

BS 476 Adhered\*

BS 476 Unadhered\*

CAN ULC S102 Adhered

CAN ULC S102 Unadhered

EN 13501 Adhered\*

EN 13501 Unadhered\*

GB 8624 Adhered\*

ISO 5660 Adhered

\*passes with additional treatment

Lightfastness: AATCC 16.3, 100+ hours



Specifications  
Tek-Wall Lucent  
300066

**maharam**

**Environmental**

Greenguard Gold Certified  
REACH Compliant  
Contains Recycled Content  
FR Free

**Warranty**

10 years: Walls  
3 years: Upholstered Walls.

© 2020 Maharam


Complete product information at [maharam.com](http://maharam.com)  
800.645.3943



001 Icefall



002 Village



003 Ammonite



004 Mythical



005 Darkness



006 Chalkboard



007 Riverway



008 Aventurine



010 Ecstatic



011 Arrowhead



012 Ironbark



013 Merriment



014 Sundress



015 Cloudberry