

## Stratum XI


Collection	<b>Stratum</b>	
Style Number	<b>034UV</b>	
Construction	<b>Multilayer WPC With Attached Cork Underlayment</b>	
Class / ASTM F3261	<b>Class III, Type B</b>	
Attached Underlayment	<b>Cork</b>	
Finish	<b>ExoGuard®</b>	
	U.S.	Metric
Nominal Dimensions	<b>9 in w x 72 in l</b>	<b>23 cm w x 183 cm l</b>
Actual Dimensions	<b>8.98 in w x 72.05 in l</b>	<b>22.81 cm w x 183.01 cm l</b>
Wear Layer Thickness	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Overall Thickness	<b>0.319 in</b>	<b>8.1 mm</b>
Edge Profile	<b>Micro-Bevel</b>	
Installation Type	<b>Click</b>	
Installation	<b>Floating Or Direct Glue</b>	
Recommended Adhesive	<b>4200 1 Gallon, 4200 4 Gallon, 2200 4 Gallon, 2200 1 Gallon or 4151</b>	



### Packaging

Pieces per Carton	<b>6 pcs</b>	
Area per Carton	<b>26.95 sq ft</b>	<b>2.5 sq m</b>
Weight per Carton	<b>53.09 lbs</b>	<b>24.08 kg</b>

### Recommended Installation Method



### Coordinating Products

COREtec: Stratum 500, Stratum 700, Stratum Eiris, Defined

### Warranties

[15 Year Commercial Limited Warranty](#)

### Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

## Material Health & Environmental Certifications

---

### Health & Wellbeing

Material Ingredient Transparency  
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | Certified  
Greenguard Gold | Certified

### Climate Impact

Environmental Product Declaration (EPD)  
  
Embodied Carbon (Cradle to Gate)  
Total Recycled Content

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017  
11.2 Kg CO<sub>2</sub>/M<sup>2</sup>  
0% (Pre-Consumer 0% | Post-Consumer 0%)

### Global Product Assessment

Country of Origin | Imported

## WELL V2 Contribution Credit

---

X01 Fundamental Material Precautions  
Part 1: (C): Restrict Asbestos Precondition

**Absence of Asbestos**

X08 Hazardous Material Reduction  
Part 1: Limit Hazardous Materials Optimization

**Absence of Heavy Metals**

X10 Volatile Compound Reduction  
Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

**Absence of Halogenated Flame Retardants**

X10 Volatile Compound Reduction  
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

**Ortho-Phthalates**

X11 Long Term Emissions Control  
Part 2: Flooring Optimization

**FloorScore & Greenguard Gold Certified**

X14 Material Transparency  
Part 1: Promote Ingredient Disclosure Optimization

**Health Product Declaration (HPD) | 1000 Ppm Disclosure**

## Leed v4 Contribution Credits

---

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 1: Material Ingredient Reporting

**Health Product Declaration (HPD) | 1000 Ppm Disclosure**

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

**FloorScore & Greenguard Gold Certified**

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways

---



Beacon Hill Oak 00604



Fort Hill Oak 00609



Newbury Oak 00611



Fenway Oak 00615

