

Traction Aqua


Collection	TractionSafety	
Style Number	4493V	
Welding Rod Style Number	184CA	
Construction	Commercial Slip-Resistant Sheet	
Finish	ExoGuard®	
	U.S.	Metric
Overall Thickness	0.079 in	2 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	S150-95, 4200 1 Gallon, 4200 4 Gallon, Weld Rod 320', 2200 or 4151	

Packaging

Actual Roll Size	6.56 ft w x 65.62 ft l	2.00 m w x 20.00 m l
Area per Roll	47.84 sq/roll	40 sq m/roll
Weight per Roll	238.09 lbs	108 kg



Recommended Installation Method



Reverse

Coordinating Products

Sheet: Traction Sole

Performance + Testing

Static Load (ASTM F970)	Passes (Modified), *2000 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Resistance to Heat (ASTM F1514)	Passes	
Resistance to Light (ASTM F1515)	Passes	
Resistance to Chemicals (ASTM F925)	Passes	
Smoke Density (ASTM E662, Flaming Mode)	Passes	
Radiant Panel (ASTM E648)	Passes, Class I	
Coefficient of Friction (ASTM D2047, Slip Resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	
Enhanced Slip Resistance / AS 4586 Appendix D	R11	
Enhanced Slip Resistance / DIN 51130/EN 16165 Annex B	R11	
Enhanced Slip Resistance / AS 4586 Appendix A	P4	
Enhanced Slip Resistance / RRL Pendulum Test	50+	
Enhanced Slip Resistance / EN 13845	ESf	
Enhanced Slip Resistance / Surface Roughness	20	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.
Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +52 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

Warranties

10 Year Commercial Limited

Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient

Material Health & Environmental Certifications

Health & Wellbeing

Material Ingredient Transparency

Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure

FloorScore® | Certified

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

Life-Cycle Carbon Emissions

Total Recycled Content

3rd Party Certified in Accordance to ISO 14044 And 14071

7.48 Kg Co₂/M²

Low Embodied Carbon

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions

Part 1: (C): Restrict Asbestos Precondition

Absence of Asbestos

X08 Hazardous Material Reduction

Part 1: Limit Hazardous Materials Optimization

Absence of Heavy Metals

X10 Volatile Compound Reduction

Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

Absence of Halogenated Flame Retardants

X10 Volatile Compound Reduction

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

Ortho-Phthalates

X11 Long Term Emissions Control

Part 2: Flooring Optimization

FloorScore Certified

X14 Material Transparency

Part 1: Promote Ingredient Disclosure Optimization

Health Product Declaration (HPD) | 1000 Ppm Disclosure

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization

Material Ingredients - Option 1: Material Ingredient Reporting

Health Product Declaration (HPD) | 1000 Ppm Disclosure

MR Credit: Building Product Disclosure and Optimization

Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

EQ Credit: Low Emitting Materials

Option 1: Product Category Calculations

FloorScore Certified

Installation Guidelines

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways




Share 00104
Weldrod 25202



Dash 00114
Weldrod 25772



Nurture 00130
Weldrod 25212



Assist 00496
Weldrod 24490



Prosper 00518
Weldrod 25764



Goodness 00761
Weldrod 25762

