



CALLA® Templok®

Tegular and Square Lay-In
smooth texture



**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Calla® Templok Square Tegular panels with Suprafine® 9/16" suspension system

Learn How Templok
Ceilings Save Energy!



Smooth texture mineral fiber ceiling combines exceptional acoustical performance, energy savings and enhanced thermal comfort using advanced Phase Change Material (PCM) technology.

KEY SELECTION ATTRIBUTES

- Saves up to 15% energy*
- Improve thermal comfort with ceilings that help regulate indoor temperatures
- Provides up to 35 BTUs/SF of passive cooling*
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Exceptional sound-blocking performance for enhanced speech privacy: CAC 39
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Energy-saving, high light-reflective finish
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

TYPICAL APPLICATIONS

- Office
- Education
- Transportation
- Healthcare

* Measured cooling energy savings in lab test. Results may vary. See Templok Technical Guide.

COLOR



White
(WH)

DETAILS (Other suspension systems compatible. Refer to listing on next page.)



1. Calla® Templok® Square Tegular panel
2. Calla Templok back of panel
3. Calla Templok with Suprafine® 9/16" suspension system



Save up to 50% in Tax Credits

Templok® ceilings may qualify for Investment Tax Credits (ITC) under Inflation Reduction Act of 2022, Section 48E

Learn more at armstrongceilings.com/saveontemplok

TechLine 877 276-7876

armstrongceilings.com/callatemplok

Armstrong®
World Industries



CALLA® Templok®

Tegular and Square Lay-In
smooth texture

LEED® WELL LBC

UP TO 41% RECYCLED CONTENT

energy management

construction waste mgmt

regional materials

design for flexibility

EPD

recyclable/ bio-based materials

recycled content

sourcing of raw materials

material ingredient reporting

low emitting/ materials

lighting quality

acoustics

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
CALLA® Templok® 9/16" Square Tegular		2824TEMP (Field Panel Only – cannot be cut)	24 × 24 × 1-1/4"
		2824 Use 2824 for borders and cutting needs. See Calla Tegular Data Page for Product Details	24 × 24 × 1"
CALLA® Templok® 15/16" Square Tegular		2822TEMP (Field Panel Only – cannot be cut)	24 × 24 × 1-1/4"
		2822 Use 2822 for borders and cutting needs. See Calla Tegular Data Page for Product Details	24 × 24 × 1"
CALLA® Templok® 15/16" Square Lay-in		2820TEMP (Field Panel Only – cannot be cut)	24 × 24 × 1-1/4"
		2820 Use 2820 for borders and cutting needs. See Calla Square Lay-In Data Page for Product Details	24 × 24 × 1"

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$\$

NRC + CAC =		Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY					Recycle Program	30-Yr Warranty
Fog	Wash	Impact	Scratch	Soil											
0.85	39	BEST	Class A**	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	39	BEST	Class A**	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	39	BEST	Class A**	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

** Consult a code official in your jurisdiction for mechanical code compliance.

SUSPENSION SYSTEMS

15/16"					
	Prelude® XL®	Silhouette® XL® 1/4" Reveal	Silhouette® XL 1/8" Reveal	Suprafine®	Interlude® XL® HRC

Blizzard White – Suspension System Finish

A color and texture coordinated suspension system to complement Calla® ceiling panels for a monolithic look and feel.

PHYSICAL DATA

Material

Wet-formed mineral fiber with acoustically transparent membrane and virgin PVC with salt hydrate

Surface Finish

Acoustically transparent membrane with factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 450 or less.

ASTM E1264 Classification

Type A, Form A2.2, Pattern G

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.

Thermal Energy Storage Capacity

Stores a minimum of 35 BTU/SF from 62°F to 83°F per ASTM C1784-20

VOC Emissions

Compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance

CAC testing conducted using Silhouette® suspension system for 9/16" edge detail.

Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Twenty (20) Year Limited Thermal Energy Storage Capacity Warranty

Weight: Square Feet/Carton

2824TEMP, 2822TEMP, 2820TEMP - 2.25 LBS/SF; 16 SF/CTN

Minimum Order Quantity

1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/callatemplok
BPCS-7173-525

LEED® is a registered trademark of the U.S. Green Building Council; Living Building Challenge® (LBC) is a registered trademark of the International Living Future Institute; WELL® and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard