



Calla® Ceiling Panels

Armstrong World Industries

Final Assembly: Pensacola, Florida, USA
Life Expectancy: 30 Year(s)
Embodied Carbon: 0.305kg CO2eq 
Declared Unit: 1 square ft.
End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program)

Ingredients:

Mineral Wool; Perlite ore; Corn Starch; Clay; Cellulose; Calcium Carbonate; Limestone; Aluminum hydroxide; Aluminum Trihydrate; Polyvinyl acetate; Titanium dioxide; Acrylic Acid; Calcium carbonate; Barium sulfate; Propanol; Starch; Polyvinyl alcohol; Kaolin; Silica; Diatomaceous Earth; Quartz; Mica; Amorphous Silica; Sodium Salt; Hydroxyethylcellulose; Polyethylene Wax; Black Tint; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Silisic Salt; Attapulgitic Clay; Iron Oxide; Water; Methylpropanoate; Polyethylene; Butanamide, N-(4-chloro-2,5-dimethoxyphenyl)-2-[[2,5-dimethoxy-4-[(phenylamino)sulfonyl]phenyl]azo]-3-oxo-

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☒ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Applicable

ARM-0001
EXP. 01 APR 2026
Original Issue Date: 2016