

LYRA®
Vector®
smooth texture

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



DESIGNFlex®
A New World of Choice
for Ceiling Systems

plus capabilities
to do more



armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Lyra Vector panels with Prelude XL 15/16" suspension system

Smooth, drywall-like visual with a 1/4" reveal and downward accessibility; ideal for projects where plenum space is limited. Offers high sound absorption.

KEY SELECTION ATTRIBUTES

- DesignFlex® options include made-to-order sizes and colors available to ship in 3 weeks
- 1/4" reveal between acoustical panels results in a monolithic appearance
- Vector Trim Kit in Blizzard White finish for easy installation and bright visual
- Downward accessible for minimal plenum height
- Outstanding acoustical performance for open plan areas, both Articulation Class 190 and NRC 0.90
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Coordinates with Calla® Total Acoustics panels for the ideal combination of sound absorption and sound blocking
- Smooth, clean durable finish – Washable Scratch-resistant Soil-resistant
- Energy-saving high light-reflective finish
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Available with factory-cut holes for USAI® trimless downlight fixture integration
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLORS Due to printing limitations, shade may vary from actual product.



DETAILS



1. Lyra® Vector® with Prelude® XL® 15/16" suspension system

TechLine 877 276-7876
armstrongceilings.com/lyra

Armstrong®
World Industries

LYRA®
Vector®
smooth texture

LEED®
WELL + LBC


UP TO 71% RECYCLED CONTENT

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/biobased materials
producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting materials
lighting quality
acoustics

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimen- sions
LYRA® 15/16" Vector® with 1/4" Reveal 	73	8494	24 × 24 × 7/8" 
		8495	24 × 48 × 7/8" 
		8496	24 × 72 × 7/8" 
		8497	24 × 96 × 7/8" 
		8498	30 × 30 × 7/8" 
		8499	48 × 48 × 7/8" 
		7/8" Thick – 15/16" Vector	
Made-to-Order Sizes	1 Ctn Min FAST SIZE 3 WEEKS order to ship	Width (short side)	Length (long side)
Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com		4" – 30" 30-1/16" – 48"	9" – 120" 30-1/16" – 48"

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
* Advertised values for light reflectance, wash and scratch resistance are applicable to white tiles only

TRIM KITS FOR VECTOR® PANELS

Item No.	Color	Length	Substrate	PCS/CTN
VETK4ZW	Blizzard White	4"	Steel	24
VETK6ZW	Blizzard White	6"	Steel	24
VETK24ZW	Blizzard White	24"	Steel	24
VETK48ZW	Blizzard White	48"	Steel	24
VETK96ZW	Blizzard White	96"	Steel	24

Made-to-Order Sizes & Colors

4-6 WEEKS order to ship

Length
4" – 96"

PHYSICAL DATA

Material
Fiberglass with acoustically transparent membrane

Surface Finish
Acoustically transparent membrane with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type B, Form B2, Pattern G; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Design Considerations
Use fixture trim kit around all lights, diffusers, and other ceiling penetrations to avoid exposed suspension system and panel edges.
Physical product samples for standard and custom colors are available upon request. Please refer to the physical product sample prior to making a final selection. While we strive to ensure exact color matches, various factors such as differences in materials, texture, substrate porosity, painting processes, lighting, and observer subjectivity can all affect how paint colors appear on ceiling and wall panels, suspension systems, and trim products. Due to these and other differences, ceiling and wall panels, trim products, and suspension systems with the same color name will coordinate but may not be an exact color match. Product is dye-lotted. Order sufficient initial quantities and attic stock to minimize possible color variation.

Insulation Value
R Factor – 3.5 (BTU units); R Factor – 0.62 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
8494 – 0.58 LBS/SF; 48 SF/CTN
8495, 8497 – 0.56 LBS/SF; 96 SF/CTN
8496 – 0.57 LBS/SF; 72 SF/CTN
8498 – 0.59 LBS/SF; 75 SF/CTN
8499 – 0.60 LBS/SF; 64 SF/CTN

Minimum Order Quantity
1 carton

