

360° PAINTED GRID

Suspension System



360° Painted Grid System with Axiom® Classic Perimeter Trim

This 9/16" and 15/16" profile suspension system is used to define open plenum spaces, or used as decorative accent on clouds and canopies.

KEY SELECTION ATTRIBUTES

- Helps to define space in an open/exposed plenum concept
- Available in Suprafine® 9/16" and Prelude® 15/16" profiles
- PeakForm® profile increases strength and stability for improved performance during installation
- 360 Pre-qualified colors are part of the sustain portfolio.
- SuperLock™ main beam clip is engineered for a strong, secure connection and fast, accurate alignment confirmed with an audible click; easy to remove/relocate
- Hot-dipped galvanized coating inhibits red rust better than electrogalvanized or painted systems
- Choice of matte and gloss finishes**
- XL® staked-on end detail provides secure locked connection; easy to remove, reuse, and relocate
- All acoustical grid and Axiom trim accessories (a.k.a. clips) are supplied as unpainted items. Exposed clips will need to be field painted after installation, if required for the project. See design considerations below for more information.
- 10-Year Limited Warranty



COLORS AND FINISHES



Available in any color!

NOTE: Colors that are pre-qualified to meet Sustain™ portfolio requirements are available upon request. Other made-to-order colors must be evaluated if sustainability criteria is required. Custom colors are available, for options contact Specials, abpspecials@armstrongceilings.com

360° PAINTED GRID

Suspension System

Declare.

LEED® WELL | LBC

UP TO 30% RECYCLED CONTENT

energy management

construction waste mgmt

regional materials

design for flexibility

EPD

recyclable/producer resp.

biobased materials

recycled content

sourcing of raw materials

material ingredient reporting

low emitting materials

lighting quality

acoustics

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

VISUAL SELECTION

				HANGER SPACING* LBS/LF	
Item No. ♦	Description	Rout Spacing	Dimensions (Inches)	4 FT.	5 FT.
360° Painted Baked Polyester Paint for Exposed Grid Applications Available in White and Black Only					
Prelude® XL® 15/16" (grid end detail not painted)	730136_ _	12' HD Main Beam	24" O.C.	144 × 15/16 × 1-11/16"	16.73
	XL734036_ _	4' Cross Tee	24" O.C.	48 × 15/16 × 1-11/16"	12.25
	XL732036_ _	2' Cross Tee	N/A	24 × 15/16 × 1-11/16"	61.33 @ 2'
Suprafine® XL® 9/16" (grid end detail not painted)	750136_ _	12' HD Main Beam	24" O.C.	144 × 9/16 × 1-11/16"	16.86
	XL754036_ _	4' Cross Tee	24" O.C.	48 × 9/16 × 1-11/16"	10.34
	XL752036_ _	2' Cross Tee	N/A	24 × 9/16 × 1-11/16"	51.83 @ 2'
Molding	780036_ _	12' Hemmed Angle Molding	N/A	144 × 7/8 × 7/8"	N/A
	780436_ _	12' Hemmed Angle Molding	N/A	144 × 9/16 × 7/8"	N/A

Custom 360° Grid for Exposed Grid Applications



Custom 360° Colors

Available in custom 360 painted finish, for options contact Specials, abpspecials@armstrongceilings.com

Custom 360° Powder Coated Grid for Installations with Matching Axiom and Suspension Systems Painted to match Axiom Trim

Prelude XL 15/16"	AX73013_ _	12' HD Main Beam	24" O.C.	144 × 15/16 × 1-11/16"	16.73	8.73
	AX73403_ _	4' Cross Tee	24" O.C.	48 × 15/16 × 1-11/16"	7.8	N/A
	AX73203_ _	2' Cross Tee	N/A	24 × 15/16 × 1-11/16"	36.0 @ 2'	N/A
Suprafine® XL® 9/16"	AX75013_ _	12' HD Main Beam	24" O.C.	144 × 9/16 × 1-11/16"	16.86	10.62
	AX75403_ _	4' Cross Tee	24" O.C.	48 × 9/16 × 1-11/16"	10.34	N/A
	AX75203_ _	2' Cross Tee	N/A	24 × 9/16 × 1-11/16"	51.83 @ 2'	N/A
Molding	AX78003_ _	12' Hemmed Angle Molding	N/A	144 × 7/8 × 7/8"	N/A	N/A

- ♦ When specifying or ordering items with a color or finish, add the two-or three-letter suffix to the end of the item number (e.g. 79013 **L** **G** _ - Light Grey)
 * Simple Span
 ** Powder-coated paint only

PERFORMANCE

Seismic Category DEF	Fire Guard™	CleanAssure™ Disinfectable Panels			
		Fog	Spray	Wipe	
*	N/A	*	*	*	
*	N/A	*	*	*	
*	N/A	*	*	*	
*	N/A	*	*	*	
*	N/A	*	*	*	
*	N/A	*	*	*	

PACKAGING

Pieces/ Carton	LF/ Carton
20	240
60	240
60	120
20	240
60	240
60	120
30	360
30	360

Dots represent high level of performance.

ASTM Class
 HD - Heavy-duty
 ID - Intermediate-duty
 LD - Light-duty


DETAILS



Baked Polyester



Custom 360 Painted Colors



PHYSICAL DATA

Material
 Hot dipped galvanized steel
Surface Finish
 2.0 mil powder-coated painted surface or baked polyester paint
 Manufactured and tested in accordance with ASTM C635
Cross Tee/Main Beam Interface
 Override
End Detail
 Main Beam: Staked-on clip
 XL® Cross Tee: Staked-on clip

Seismic Restraint

NOTE: For floating installations refer to ASCE 7-10 for seismic requirements.

Main Beams	Minimum LBS. to pull out compression/tension
730136/750136	330.0
Cross Tees	Minimum LBS. to pull out compression/tension

All XL cross tees exceed 300 lbs. in compression/tension

Installation Consideration

If pop riveting must be used on powder-coated material, pre-drill with a sharp 1/8" drill bit to minimize potential paint chipping.
 If additional routs are needed for installation, please use the Field Rout Tool (item 7876) or the GC3W clip.

Design Considerations

All acoustical grid and Axiom trim accessories (a.k.a. clips) are supplied as unpainted items for baked polyester and powder-coated grid. Exposed clips will need to be field painted after installation, if required for the project. This ensures accessories meet the tested performance criteria and adhere to AWI installation instructions and warranted products or systems.

ICC Reports

For areas under ICC jurisdiction, see ICC evaluation report number ESR-1308 for allowable values and/or conditions of use concerning the suspension system components listed on this page. The report is subject to reexamination, revisions, and possible cancellation.

Warranty

See warranty details in the back of this catalog

TechLine / 1 877 276-7876
armstrongceilings.com/360paint
 BPCS-3634-725

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute; WELL™ and Well Building Standard™ are trademarks of the International WELL Building Institute; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
 World Industries