



Installation Method



Ashlar

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Bound By Thread I **Color** Cream **Collection** Dressed Lines Coordinates  
**Backing** GlasBac™

Product Specifications		
Product Number	125950AK00	
Product Construction	Engaged Tufted Pattern Loop	
Yarn System	100% Recycled Content Nylon	
Yarn Manufacturer	Aquafil	
Dye Method	100% Solution Dyed	
Soil/Stain Protection	Protekt <sup>2</sup> ®	
Preservative Protection	Intersept®	
More Product Specifications		
	Imperial	Metric
Tufted Yarn Weight	24 oz/yd <sup>2</sup>	814 g/m <sup>2</sup>
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.151 in	3.8 mm
Pile Thickness	0.102 in	2.6 mm
Stitches	10 /in	39.37 ends/10cm
Pile Density	8,471 oz/yd <sup>3</sup>	314,103 g/m <sup>3</sup>
Size	9.845 in x 39.38 in	25cm x 1m
Performance Specifications		
Flooring Radiant Panel	(ASTM E-648) Passes	
Smoke Density	(ASTM E662) ≤ 450	
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's	
Static	(AATCC - 134) < 3.0 KV	
Dimensional Stability	AACHEN Din 54318 < 0.10%	
Traffic Classification	Severe	
Fiber Modification Ratio	1.9 to 2.2	
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition	
Health + Environmental Specifications		
Embodied Carbon (Cradle to Gate)	5.09 Kg CO <sub>2</sub> /M <sup>2</sup>	
Total Recycled Content	70.08 %	
Recycled Content (Pre Consumer)	58 %	
Recycled Content (Post Consumer)	12.09 %	
Indoor Air Quality	<a href="#">Green Label Plus #GLP0820</a> CDPH 01350	
Material Composition	Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.	
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>	
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>	
Environmental Certifications	<a href="#">NSF/ANSI 140 Gold</a> <a href="#">GreenCircle Certified Recyclable</a>	
LEED v4	Contributes to multiple IEQ and MR credits	
End of Life	Carpet to Carpet Recycling through ReEntry®	
Technical Information		
Installation	<a href="#">Interface Installation Guidelines</a>	
Maintenance	<a href="#">Recommended Interface Maintenance Guidelines</a>	
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)	
Warranty	<a href="#">15 Year Standard Carpet Warranty</a>	
Installation Method	Ashlar	
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified facilities in Troup County, Georgia, United States</a>	