



Installation Method



Ashlar



Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product	Crossroads 4.5 mm	Color	Stepping Stone	Collection	Earthen Forms Collection
Product Specifications					
Product Number	A034				
Product Construction	High Performance Luxury Vinyl Tile				
Class / ASTM F1700	Class III Printed Vinyl Tile				
Wear Layer Thickness	22 mil				
Total Thickness	4.5 mm				
Backing Class	Commercial Grade				
Finish	Ceramor™				
Nominal Dimensions	25 cm x 1 m (9.845 in x 39.38 in)				
Performance Specifications					
IIC Sound Rating	(ASTM E492-09) 64 IIC				
Slip Resistance	(ASTM D2047) >0.55 wet/dry, ADA Compliant				
Static Load Limit	(ASTM F970) 1500 psi				
Flexibility	(ASTM F137) Passes				
Resistance to Heat	(ASTM F1514) Passes				
Resistance to Light	(ASTM F1515) Passes				
Radiant Flux	(ASTM E648) Class I				
Smoke Density	(ASTM E-662) ≤ 450				
Size & Squareness	(ASTM F2055) Passes, +/- 0.016 in. per linear foot				
Thickness	(ASTM F386) Passes				
Dimensional Stability	(ASTM F2199) Passes				
Residual Indentation	(ASTM F1914) Passes				
Resistance to Chemicals	(ASTM F925) Passes				
Health + Environmental Specifications					
Embodied Carbon (Cradle to Gate)	9.2 Kg CO ₂ /M ²				
Total Recycled Content (Pre Consumer)	39%				
Indoor Air Quality	GREENGUARD Gold FloorScore® SCS-FS-04366 CDPH 01350 compliant				
Material Composition	Free of Ortho Phthalates, Added Formaldehyde and Heavy Metal Stabilizers				
Disclosure of Environmental Impacts	Environmental Product Declaration				
Disclosure of Product Ingredients	Health Product Declaration				
Environmental Certifications	NSF/ANSI 332, Meets Certification Guidelines				
LEED v4	Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR				
Packaging					
Quantity per Carton	26.91 ft ² (2.5 m ²)				
Pieces per Carton	10				
Weight Per Carton	48 lb (22 kg)				
Cartons per Pallet	40				
Pallets per Truckload	20				
Technical Information					
Installation	Interface LVT Installation Guidelines				
Maintenance	Recommended Interface LVT Maintenance Guidelines				
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)				
Warranty	15 Year Standard LVT Warranty				
Installation Method	Ashlar Herringbone				