


Installation Method



Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product	Monochrome	Color	Cream	Backing	GlasBac™
Product Specifications					
Product Number	1385702500				
Product Construction	Tufted Textured Loop				
Yarn System	100% Recycled Content Nylon				
Yarn Manufacturer	Aquafile				
Dye Method	100% Solution Dyed				
Soil/Stain Protection	Protekt ² ®				
Preservative Protection	Intersept®				
More Product Specifications					
	Imperial		Metric		
Tufted Yarn Weight	24 oz/yd ²		814 g/m ²		
Machine Gauge	1/12 in		47.2 ends/10cm		
Pile Height	0.18 in		4.60 mm		
Pile Thickness	0.12 in		3.00 mm		
Stitches	10.30 /in		40.55 ends/10cm		
Pile Density	7,261 oz/yd ³		269,236 g/m ³		
Size	19.69 in x 19.69 in		50cm x 50cm		
Performance Specifications					
Flooring Radiant Panel	(ASTM E-648) Passes				
Smoke Density	(ASTM E-662) ≤ 450				
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's				
Static	(AATCC - 134) < 3.0 KV				
Dimensional Stability	AACHEN Din 54318 < 0.10%				
Traffic Classification	Heavy				
Fiber Modification Ratio	1.9 to 2.2				
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition				
Health + Environmental Specifications					
Embodied Carbon (Cradle to Gate)	5.09 Kg CO ₂ /M ²				
Total Recycled Content	69.83 %				
Recycled Content (Pre Consumer)	57.87 %				
Recycled Content (Post Consumer)	11.96 %				
Indoor Air Quality	Green Label Plus #GLP0820				
Material Composition	Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.				
Disclosure of Environmental Impacts	Environmental Product Declaration				
Disclosure of Product Ingredients	Health Product Declaration				
Environmental Certifications	NSF/ANSI 140 Gold				
LEED v4	Contributes to multiple IEQ and MR credits				
End of Life	Carpet to Carpet Recycling through ReEntry®				
Technical Information					
Installation	Interface Installation Guidelines				
Maintenance	Recommended Interface Maintenance Guidelines				
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)				
Warranty	15 Year Standard Carpet Warranty				
Installation Method	Monolithic				
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States				