

TECHNICAL SPECIFICATION

hushfree.Access.M HUS-AP-004

FOR COMFORTABLE TEAMWORK AND MEETINGS FOR 1 TO 4 PEOPLE

HushFree.Access.M is a B-rated acoustic booth, fully adapted to the needs of people with disabilities. The pod has a low threshold, enabling easy and relaxed entry, a wider door, and a handle allowing easy booth opening. HushFree.Access.M has a new LED lighting system with an intensity of 500 lux at the tabletop level. It is also perfect as a small, private workspace or office. You can equip the booth however you want – arrange its interior yourself.



DIMENSIONING




4





W/D/H: exterior 87.00 x 54.72 x 89.41 in
interior 78.48 x 50.55 x 83.96 in

Weight: 1167 lbs **Weight with box:** 1431 lbs

Logistic data is available on request.



1 Access to power cable



LIGHTING

LED ceiling light 20W / 4000 K, lm – 2300; lux – min. 300 / medium 500 / max. 700. Adjusted in the range of 2200 - 6500K.



hushoffice


Manufacturer: Fabryka Mebli Biurowych Mikomax sp. z o.o. | 93-231 Łódź ul. Dostawcza 4, Polska
Distributor: Mikomax sp. z o.o. | 93-231 Łódź ul. Dostawcza 4, Polska

hushoffice.com


TECHNICAL SPECIFICATION

hushfree.Access.M HUS-AP-004

T-Shaped Space in hushFree.Access.M equipped with the desk.



The empty hushFree.Access.M, without equipment, complies with ADA T-shaped space requirements.



ELECTRIC SYSTEM

LED CEILING LIGHT x2.

POWER SUPPLY MODULE (BASIC): 2x power supply, 2x RJ45.

POWER SUPPLY MODULE (OPTIONAL, AS REQUIRED): 1x type A and 1x type C charger with a total power of 5V / 25W, HDMI.

POWER CABLE: Black cable with three-prong grounded plug 110V. The product can be powered from the top or bottom (detailed information can be found in the Assembly Manual). For the power supply from the top 2.36 in milling for the power cable outlet prepared from the inside of the ceiling (not visible from outside). The total length of the cable – 16.40 ft. The cable length for the exit of unit – 11.15 ft.

LAN PLUG CAT.6: available with 16.40 ft total cable length, and available with 11.15 ft at the booth exit.

The exact dimensions for the location of the power cable outlet and the LAN CAT.6 are available on request.


MOTION SENSOR: located on the central column, activates lighting at 70% and ventilation systems at 100% of total power. Standby power consumption 5W.

Maximum power consumption of the product 5W – 64.5W.



VENTILATION SYSTEM

4 fans x 80 m³/h with a maximum airflow 188 CFM. Total air exchange 63 seconds, 57 l/s.



EXTERIOR

GLASS DOOR WITH HANDLE: acoustic, tempered and laminated safety glass 0.39 in, 5.5.2 thickness, including the 0.19 in glass, 0.07 in acoustic sheet and 0.19 in glass. Anti-collision marking – silkscreen integrated inside the 2.55 in wide glass. Transparent glass. Left or Right-handed door - option to be chosen at ordering stage. Door with magnetic closure and the possibility of adjusting the tightening force.

REAR SIDE GLASS PANELS: acoustic and laminated glass 0.39 in (RW= 34 dB), 5.5.2 thickness, including the 0.19 in glass, 0.07 in acoustic sheet and 0.19 in glass. Placed in aluminum profiles with acoustic seal. Transparent glass. Frosted version as an option.

Aluminum threshold with a drop-down seal in black RAL 9004.

DOOR HANDLE AND HINGES: painted in cosmos grey. Handle dimensions: 1.77 x 8.70 in. Left / Right-handed - option to be chosen at ordering stage.

CASE: 3-layer honeycomb board with a thickness of 1.49 in. Both sides covered with melamine and finished with ABS edging. The product structure is prepared for 4 variants of seismic anchoring for 2 types of concrete substrates, SLWC (sand-lightweight concrete) and NWC (normal weight concrete). Full seismic report available on request.

HUSHDOOR.LIMITER: door opening limiter. Mounted on the lower and upper hinge (2 pieces). After mounting, the acoustic cabin door opens to a maximum angle of 130 degrees. Made of black EPDM material with a hardness of 50° ShA.

15 feet as standard.



hushoffice

Manufacturer: Fabryka Mebli Biurowych Mikomax sp. z o.o. | 93-231 Łódź ul. Dostawcza 4, Polska
Distributor: Mikomax sp. z o.o. | 93-231 Łódź ul. Dostawcza 4, Polska

hushoffice.com

TECHNICAL SPECIFICATION

hushfree.Access.M HUS-AP-004

INTERIOR

ROLLED CARPET: Product installation (optional) - using the factory-supplied carpet or on the customer's floor/carpet. complies with ASTM D2859 – 16 (2021), standard test method for ignitability characteristics of ready to use textile floor covering materials. Adapted to commercial intensive use (hotel room, hotel suite, boutique, shop, restaurant, conference room, high traffic office, reception, stairs). Graphite color.

INTERIOR PANELS: Made as a composite based on PETFELT, polyester fleece and fabric. PUR fire-retardant foam with acoustic properties, re-bonded.

PANELS UPHOLSTERY Athlon Plus:

weight: 750 g/lm — 24.19 oz/lin.yd; **composition:** 56% polyester, 44% Trevira CS; **flammability:** cigarette (BS EN 1021-1), cigarettes and matches (BS EN 1021 1&2), CA TB 117-2013; **light fastness:** 5 (EN ISO 105B02); **pilling resistance:** 5 (EN ISO 12945-2); **abrasion resistance:** 100.000 martindale cycles (EN ISO 12947-2); **certification:** OEKO-TEX® STANDARD 100.

SOFAS UPHOLSTERY Athlon:

weight: 750 g/lm — 24.19 oz/lin.yd; **composition:** 100% polyester; **flammability:** cigarette (BS EN 1021-1), CA TB 117-2013; **light fastness:** 5 (EN ISO 105B02); **pilling resistance:** 5 (EN ISO 12945-2); **abrasion resistance:** 100.000 martindale cycles (EN ISO12947-2); **certification:** OEKO-TEX® STANDARD 100.

PANEL WITH CEILING LIGHT: in cosmos grey. Total dimensions 7.48 x 25.19 in, ceiling light dimensions: 2.75 x 25.19 in, hole prepared for smoke detector diameter 0.78 in, hole prepared for sprinkler installation diameter 2.55 in.

ELECTRICAL PLUGS DIAMETER: 3.70 in.

HUSHASSISTANT: 4-inch, round, high-resolution touchscreen to control pod settings, adjust lighting and airflow, and extend calendar reservations. Hush-Assistant can adjust brightness, color and activate scenes (moods) for different needs. Prepared for integration into the product's power supply. The system supports integration with the Microsoft 365 Business platform.

HUSHTABLE.M (optional): measuring W/D/H 30.19 x 32.95 x 28.93 in. Made of 0.70 in thick plywood covered with HPL laminate on both sides. Support leg made of 1.18 x 1.96 in steel profile, powder-coated in cosmos grey colour. Maximum load — **55 lbs.**

HUSHOCCUPANCY.SIGN (optional): booth occupancy light indicator, measuring 3.77 x 3.77 x 1.49 in, prepared to be integrated with the ventilation module power supply. Adapted to be positioned on the booth ceiling anywhere within 39.37 in of the fan housing. Actuated by a motion sensor.

HUSHSOFA.MEDIUM.RH/LH (the optional set of double freestanding sofas): seat module including backrest, available in left and right versions of 48.42 x 21.02 x 27.08 in overall dimensions. Seat height — 18.62 in, backrest height from seat — 8.46 in. Inner structure made of wood-based materials, sprung layer — 100% PU foam, fluffy fleece 100% Polyester. Outer layer - upholstery fabric. Maximum load of the sofa — 600 lbs.

HUSHSCREEN.SET (optional): adapter for mounting a TV monitor with VESA bracket (in) 2.95 x 2.95; 3.93 x 3.93; 3.93 x 7.87; 7.87 x 3.93; 7.87 x 7.87 with overall dimensions 8.70 x 8.89 x 1.77 in. Adapted for mounting on the central column of the booth by means of mounting screws which are an integral part of the column. Structure made of bent sheet metal powder-coated in cosmos grey colour. Maximum weight of TV — **48.5 lbs.** Maximum TV screen size that can be installed in the booth: **40"**.

When the hushScreen.Set is configured into the product order, an additional power outlet inside the central column is provided.

OPTIONAL EQUIPMENT	WEIGHT:	WEIGHT WITH BOX:
HUSHSOFA.MEDIUM.RH /LH (1 PC.)	45.41 lbs	54.23 lbs
HUSHTABLE.M	21.82 lbs	23.14 lbs
HUSHSCREEN.SET	5.07 lbs	5.29 lbs

ACOUSTIC RATING

Frequency range 125 Hz to 8000 Hz according to ISO 23351-1:2020. Speech level reduction — D_{SA} 26.4 dB.

SEISMIC ANCHORAGE

Product with Seismic Anchoring capability as standard solution. Instructions on how to anchor are available on request.

SUSTAINABLE DEVELOPMENT

Hushoffice booths are manufactured in the ISO 9001 and 14001 certified production factory in Poland by Mikomax Smart Office. The production process complies with the ISO 14001 environmental management system standard. Hushoffice booths are packaged and delivered in lightweight, recyclable cardboard boxes.

CERTIFICATION



warranty



hushoffice

Manufacturer: Fabryka Mebli Biurowych Mikomax sp. z o.o. | 93-231 Łódź ul. Dostawcza 4, Polska
Distributor: Mikomax sp. z o.o. | 93-231 Łódź ul. Dostawcza 4, Polska

hushoffice.com