COLORADO
STONE QUARRIES

IMPORTANT NOTICE

Please note that all Colorado Stone Quarries marble is a moisture sensitive marble.

Therefore, for installation, selected setting material or equivalent are NEEDED for a proper installation: White Improved Modified Dry-Set Cement Mortar, for Large and Heavy Tile, Non-Sag, Rapid-Setting (Mapei Granirapid White, Mapei Ultraflex LFT Rapid White, White Laticrete Tri-Lite Rapid Thinset Mortar, Ardex N23 Microtec Rapid Set, Ardex X32 Microtec Rapid Set White or tested equivalent), compatible for moisture sensitive marble.

Please note that surface sealer is still required post installation for all natural stone. Fila MP90 Eco Plus or tested equivalent is recommended.

Our marble must be installed in accordance with the manufacturer's printed instructions and the applicable requirements of ANSI A108 series for the materials being used.

Back scratch coating/back buttering is required.

It is also strongly recommended to do a small surface test with the selected setting materials prior to moving forward with a large installation to ensure compatibility and avoid any staining or moistening issues.

NOTE: Colorado Stone Quarries makes no expressed or implied warranty for any particular use, installation procedure and maintenance practice. It is the responsibility of the installer to validate that the setting materials used for the installation are compatible with our marble.

Colorado Stone Quarries disclaims any liabilities after installation.The selection of a compatible setting material (mortar and grout) is the responsibility of the client/installer and Colorado Stone Quarries cannot be held responsible for any staining or moisture issues following the installation.

1734 Hwy 50E, Delta, CO 81416
ph. 1-970-874-6118
www.coloradostonequarries.com

USA MADE IN