



Rockfon Tropic® Rockfon

Final Assembly: Marshall County, Mississippi, USA; Cigacice, Poland

Life Expectancy: 50 Year(s)

End of Life Options: Recyclable (80%), Landfill (20%)

Ingredients:

Stone wool, biosoluble; Aluminum hydroxide; Fiberglass; Glucose; Limestone; **Phenol, polymer with formaldehyde¹**; Syrups, hydrolyzed starch; Water; Caprolactam; Lauro lactam; Polyvinyl alcohol; Undisclosed (0.073-0.856%)²; Calcium carbonate; Dodecanedioic acid, polymer with decanedioic acid, hexahydro-2H-azepin-2-one, 1,6-hexanediamine and hexanedioic acid; Hexamethylenediamine; Hexanedioic acid; Urea; **Urea, polymer with formaldehyde¹**; Clay; Residual oils (petroleum), solvent-dewaxed; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Lubricating oils (petroleum), C>25, solvent-extd., deasphalted, dewaxed, hydrogenated; n-Butyl acrylate; Styrene; Talc; Titanium dioxide; Undisclosed (< 0.094%)²; Undisclosed (< 0.033%)²; Undisclosed (< 0.011%)²

¹LBC Temp Exception RL-009 - Formaldehyde

²LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-------------------------------|
| ☐ LBC Red List Free | % Disclosed: 99.01% at 100ppm |
| ☒ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

RXL-0008

EXP. 01 JAN 2026

Original Issue Date: 2021