



Rockfon® Facett™ Rockfon

Final Assembly: Marshall County, Mississippi, USA

Life Expectancy: 50 Year(s)

Embodied Carbon: 2.43 - 13.52 kg CO2 eq. 

Declared Unit: 1 square meter

End of Life Options: Recyclable (85-95%), Landfill (5-15%)

Ingredients:

Stone wool, biosoluble; Fiberglass; Syrups, hydrolyzed starch; Water; Talc; Phenol, polymer with formaldehyde¹; Barium sulfate; Urea; Dodecanedioic acid, polymer with decanedioic acid, hexahydro-2H-azepin-2-one, 1,6-hexanediamine and hexanedioic acid; Caprolactam; Lauro lactam; Hexamethylenediamine; Hexanedioic acid; Urea, polymer with formaldehyde¹; Limestone; Undisclosed (< 0.209%)²; Residual oils (petroleum), solvent-dewaxed; Polyacrylic acid; Polyvinyl acetate; 2-Propenoic acid, 2-methyl-, C12-15-branched and linear alkyl esters, polymers with cetyl methacrylate, Me methacrylate, polyethylene glycol methacrylate branched tridecyl ether and stearyl methacrylate; Titanium dioxide; Undisclosed (< 0.042%)²; Guanidine, cyano-; Diethylene Glycol

¹LBC Temp Exception RL-009 - Formaldehyde

²LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-------------------------------|
| ☐ LBC Red List Free | % Disclosed: 99.75% at 100ppm |
| ☒ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

RXL-0020

EXP. 01 FEB 2026

Original Issue Date: 2025