



BOLT[®] 3

INSULATION BLOWING MACHINE

Lightning Fast Performance

Energize your installers with a portable, electric blow machine offering powerful performance, superior fiber conditioning, and the largest material hopper in its class. The BOLT 3 supercharges job completion times by easily moving all loosefill material types thru 150' of hose. Proper coverage in attics, walls, and cavities can be achieved lightning fast.

Features & Benefits

- Patented Spiked Auger*
- Quad Agitation System
- Large 25 ft³ Hopper
- 3" Diameter Outlet
- Air-Only and Air-and-Material Functionality
- Material Slide Control
- 100' Remote Control Cord
- Built-in Hose Storage
- Fits Thru 36" Doorway
- Four Casters With 2 Rotating Lockable
- Welded Steel Construction
- Durable Powder Coat Finish
- Air Volume Control

Safety Features

- **Emergency Stop** – Immediately shuts down power to the motor and blowers
- **Electrical Interlock** – Prevents machine operation if hopper is not in place
- **Hopper/Shelf Design** – Prevents access to rotating parts in the machine
- **Chain & Sprocket Guards** – Eliminates access to pinch points

MACHINE SPECIFICATIONS

Insulation	Fiberglass, Stone Wool, Cellulose
Power Requirements	Two 120v/15a Circuits Required Two 50' Power Cords Provided
Fiberglass Blow Rates	Maximum: 18-19 lbs./min. Conditioned: 14-15 lbs./min.
Cellulose Blow Rates	Maximum: 31-32 lbs./min. Conditioned: 24-25 lbs./min.
Load Height	59"
Height	69"
Width	32"
Depth	47"
Weight: Approx	475 lbs.

* Rates apply to material that has been properly conditioned.

ACCESSORY OPTIONS

Wireless Remote Control
3" x 50' Blow Hose
3" x 100' Hose Package
3" x 150' Hose Package
150' Remote Control Cord

Featured Details

Quad Agitation System – An industry leading design composed of three rotating agitators and a patented spiked auger* that opens the compressed loosefill material, eliminates clumps, and prepares the material for further conditioning.

Sealed Air-Lock Feeder – Sealed and pressurized air flow delivers a consistent flow of conditioned fiber.

Blower Air Control System – Variable control of the air volume aids in fine tuning the air-to-material ratio.

Material Control Slide – Secondary volume and conditioning control. Allows operator adjustment of fiber flow to the shredder.

Remote Control – Gives installer the option of selecting air only or air and fiber from the point of application.


Powder-Coat Finish – Durable, long-life protection for your investment.

Integrated Safety Features – Emergency stop switches; electrical interlock; front, rear and side guards.

Self-Aligning Sealed Bearings – High-quality bearings are used throughout the certainteed machine works product line. They are sealed to keep out dust and equipped with zerk fittings for proper maintenance.

*Patent nos. US8556200B2, US9592482B2, US10603672B2 and CA2726583C

Visit us at www.ctmachineworks.com
or call us at 800-237-7841 for more information.



Standard Equipment

- (1) BOLT® 3 Machine
- (1) 100' Remote Control Cord
- (2) 50' Power Cords

CertainTeed Machine Works offers a comprehensive line of commercial and residential insulation and fireproofing application equipment, including blowing machines, vacuums and accessories. We provide equipment installation, troubleshooting and repair, custom machine design services, and same-day shipping of spare parts.