

# Cashmere® Cashmere High NRC

## MINERAL FIBER TEXTURED PANEL

A lightly textured mineral fiber panel with an upscale appearance and effective noise reduction.

### Features & Benefits

- Finely textured panel offering an upscale appearance and excellent sound absorption (up to 0.70 NRC)
- VOC compliant to CDPH v1.2, 2017
- Cuts cleanly, leading to quicker installation and lower installation costs
- Environmental Product Declaration (EPD) available for this product
- Health Product Declaration (HPD) available for this product
- USDA Certified Biobased content at 96%
- Some products available in fire-rated (Protectone) versions
- 30-Year System Warranty when installed with CertainTeed suspension systems
- Available in 6 standard colors for item numbers CM-450, CM-454

### Attributes



SAG RESISTANT



BIOSHIELD®  
MOLD/MILDEW  
RESISTANT



EMISSION  
COMPLIANT  
CERTIFIED



LR  
0.82/0.83



RECYCLED  
CONTENT

### CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



HPD AVAILABLE



**Declare**™

Living Building Challenge Red List Free®

Declare™ is a service mark of The International Living Future Institute.

## LEED® v4

| RECYCLED CONTENT |          |          |
|------------------|----------|----------|
| CLASS A          | 70%      |          |
|                  | PRE: 68% | POST: 2% |
| PROTECTONE™      | 44%      |          |
|                  | PRE: 42% | POST: 2% |

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

**certainteed**  
SAINT-GOBAIN

Photo: East Aurora High School, East Aurora, NY




# Cashmere®, Cashmere High NRC

## MINERAL FIBER TEXTURED PANEL




### Colors



### Cashmere High NRC

| Cashmere High NRC   |         |            | FORMAT | DIMENSIONS (IN.) | NRC  | CAC | RECYCLED CONTENT | UL FIRE-RATED | LR   | PIECES/CARTON | SQ. FT./CARTON | LBS./CARTON | CARTONS/PALLET |
|---|---------|------------|--------|------------------|------|-----|------------------|---------------|------|---------------|----------------|-------------|----------------|
| Trim  |         |            |        |                  |      |     |                  |               |      |               |                |             |                |
|  | NRC .70 | CM-457NRCP | Panels | 24 x 24 x 3/4    | 0.70 | 30  | 70%              | —             | 0.82 | 14            | 56             | 63          | 16             |
|   |         | CM-497NRCP | Panels | 24 x 48 x 3/4    | 0.70 | 32  | 70%              | —             | 0.82 | 8             | 64             | 64          | 16             |
| Reveal  |         |            |        |                  |      |     |                  |               |      |               |                |             |                |
|  | NRC .70 | CM-454NRCP | Panels | 24 x 24 x 3/4    | 0.70 | 30  | 70%              | —             | 0.82 | 14            | 56             | 56          | 16             |
|   |         | CM-494NRCP | Panels | 24 x 48 x 3/4    | 0.70 | 32  | 70%              | —             | 0.82 | 8             | 64             | 64          | 16             |
| Narrow Reveal   |         |            |        |                  |      |     |                  |               |      |               |                |             |                |
|  | NRC .70 | CM-450NRCP | Panels | 24 x 24 x 3/4    | 0.70 | 30  | 70%              | —             | 0.82 | 14            | 56             | 56          | 16             |

### Cashmere

|   |                |         | FORMAT | DIMENSIONS (IN.) | NRC  | CAC | RECYCLED CONTENT | UL FIRE-RATED | LR   | PIECES/CARTON | SQ. FT./CARTON | LBS./CARTON | CARTONS/PALLET |
|---|----------------|---------|--------|------------------|------|-----|------------------|---------------|------|---------------|----------------|-------------|----------------|
| <b>Trim</b>   |                |         |        |                  |      |     |                  |               |      |               |                |             |                |
|  | <b>NRC .60</b> | CM-457  | Panels | 24 x 24 x 3/4    | 0.60 | 35  | 70%              | —             | 0.83 | 14            | 56             | 56          | 16             |
|   |                | CM-497  | Panels | 24 x 48 x 3/4    | 0.60 | 35  | 70%              | —             | 0.83 | 8             | 64             | 64          | 16             |
|   | <b>NRC .45</b> | PCM-457 | Panels | 24 x 24 x 3/4    | 0.45 | 35  | 44%              | Yes*          | 0.83 | 14            | 56             | 56          | 16             |
| <b>Reveal</b>   |                |         |        |                  |      |     |                  |               |      |               |                |             |                |
|  | <b>NRC .60</b> | CM-454  | Panels | 24 x 24 x 3/4    | 0.60 | 35  | 70%              | —             | 0.83 | 14            | 56             | 56          | 16             |
|   |                | CM-494  | Panels | 24 x 48 x 3/4    | 0.60 | 35  | 70%              | —             | 0.83 | 8             | 64             | 64          | 16             |
|   | <b>NRC .45</b> | PCM-454 | Panels | 24 x 24 x 3/4    | 0.45 | 35  | 44%              | Yes*          | 0.83 | 14            | 56             | 70          | 16             |
| <b>Narrow Reveal</b>  |                |         |        |                  |      |     |                  |               |      |               |                |             |                |
|  | <b>NRC .60</b> | CM-450  | Panels | 24 x 24 x 3/4    | 0.60 | 35  | 70%              | —             | 0.83 | 14            | 56             | 56          | 16             |
|   |                | CM-490  | Panels | 24 x 48 x 3/4    | 0.60 | 35  | 70%              | —             | 0.83 | 8             | 64             | 64          | 16             |


\* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

To specify color other than White, order by item number followed by color code. Example: CM-454 BEB. Color List: Beige Breeze – BEB, Blondewood – BLW, Silver Lining – SIL, Wet Clay – WEC, White Wash – WIW. Only available for CM-454 and CM-450 products.


**CAN'T FIND A SIZE?** Contact your local Sales Representative or call 800-233-8990.

Photo: East Aurora High School, East Aurora, NY


## Edge Details




Trim  
9/16" EZ Stab  
Elite Narrow



Trim  
15/16" EZ Stab  
Classic



Reveal Beveled  
15/16" EZ Stab  
Classic



Narrow Reveal  
Corner Bevel  
9/16" EZ Stab  
Elite Narrow

Color-coordinated suspension  
systems available

## Physical Data

### MATERIAL

Mineral Fiber

### FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

### ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type III, Form 2, Pattern F (Standard)

ASTM E1264-23: Type A, Form A1.2, Pattern F (Standard)

ASTM E1264-22: Type III, Form 2, Pattern C F (NRCP)

ASTM E1264-23: Type A, Form A1.2, Pattern C F (NRCP)

### VOC EMISSIONS

Independently certified compliant with  
California Department of Public Health  
CDPH/EHLB/Standard Method  
Version 1.2, 2017.

### INSTALLATION CONSIDERATION

Product is lot sensitive. Differing  
manufacturing dates should not be mixed  
in a single ceiling or unbroken area.

### MOLD/MILDEW RESISTANCE

BioShield® treatment included for added  
mold and mildew resistance.

### MAINTENANCE

Wipe with a soft cloth or vacuum  
with brush attachment.

### WARRANTY

10-year 104/90 Limited Warranty  
increases to 30 years when installed  
with CertainTeed suspension systems.  
Full warranty information can be  
found at [certainteed.com/warranty](https://www.certainteed.com/warranty).



## CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM  
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](https://www.certainteed.com)