

# Ecophon® Hygiene Advance™ Wall

## FIBERGLASS SMOOTH WALLS

Sound absorbing wall panel suitable for even the most demanding conditions, from intensive care units and operation rooms, to patient rooms and airtight laboratories.

### Features & Benefits

- Designed to facilitate daily cleaning with strong sanitizers and disinfectant chemicals
- Virtually zero particle emission, ensuring high indoor air quality. Suitable as a clean room component (ISO Class 3)
- Fully encapsulated in a smooth, high-performance film that is impervious to particles and water to repel dirt
- Quick and easy installation; stainless steel wall brackets screw into place, and wall panel simply slides into the brackets
- Easy removability allows 360-degree cleaning of the panels and the wall behind them
- Satisfies FGI Guidelines for use in restricted areas (such as operating rooms)
- Excellent sound absorption with a 0.90 NRC
- Install vertically (2-brackets) or horizontally (4-brackets)

### Attributes



**MOLD/MILDEW  
RESISTANT  
INHERENT**



**EMISSION  
COMPLIANT  
CERTIFIED**



**RECYCLED  
CONTENT**



**WASHABLE W/  
SANITIZING  
CHEMICALS**

## LEED® v4

RECYCLED CONTENT	38%	
	PRE: 0%	POST: 38%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ EQ: Low-emitting Materials


LEED® is a registered trademark of the U.S. Green Building Council.

### CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE




Hygiene Advance™ Wall		COLOR	DIMENSIONS MM(IN.)	NRC	SABINS/ UNIT	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. M (FT.)/ CARTON	LBS./ CARTON
Wall Panel										
	3713 8030	White	592 x 1192 (≈ 23-5/16 x 46-15/16)	0.90	6.8	0.73	38% post	6	46	39

### Accessories

HYGIENE ADVANCE WALL ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE
	2630 0716 Connect Wall Fixing (stainless steel)	12	2 per panel for vertical installation, 4 per panel for horizontal installation

### Edge Details



### Physical Data

**MATERIAL**  
Fiberglass  
Fully-encapsulated in a smooth, impervious high-performance film

**FLAME SPREAD/SMOKE DEV.**  
Per ASTM E84 — CAN/ULC S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less  
(Class A per ASTM E1264)

**VOC EMISSIONS**  
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

**MOLD/MILDEW RESISTANCE**  
Fiberglass substrate is fully-encapsulated by water-impervious film.

**MAINTENANCE**  
Refer to online maintenance instructions.

**WARRANTY**  
10-year Ecophon Warranty.  
Full warranty information can be found at [certainteed.com/warranty](https://certainteed.com/warranty).



**CertainTeed**  
CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM  
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](https://certainteed.com)