



School Board®

MINERAL FIBER FISSURED PANEL

A mineral fiber panel with high impact resistance and high light reflectance, ideal in educational settings.

Features & Benefits

- Up to 25% higher surface hardness than conventional wet-felted ceiling products per ASTM C 367 testing
- Environmental Product Declaration (EPD) available for this product
- Available in (Protectone) version suited for fire assemblies
- Shares surface pattern with other Fine Fissured products
- Health Product Declaration (HPD) available for this product
- School Board has USDA Certified Biobased content at 96%
- 30-Year System Warranty when installed with CertainTeed suspension systems

Attributes

				
SAG RESISTANT	BIOSHIELD® MOLD/MILDEW RESISTANT	EMISSION COMPLIANT CERTIFIED	LR 0.84	RECYCLED CONTENT 33-44%

CERTIFICATIONS & PRODUCT DECLARATIONS

		
EPD AVAILABLE	HPD AVAILABLE	

DeclareSM
Living Building Challenge Red List Free®
DeclareSM is a service mark of The International Living Future Institute.

LEED® v4

RECYCLED CONTENT		
CLASS A PROTECTONE®	33%	
	PRE: 28%	POST: 5%
	44%	
	PRE: 42%	POST: 2%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Environmental Product Declarations (EPDs)

LEED® is a registered trademark of the U.S. Green Building Council.


School Board

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
Trim												
	NRC .55	FFSB-157	Panels	24 x 24 x 5/8	0.55	35	33%	—	16	64	47	20
		FFSB-197	Panels	24 x 48 x 5/8	0.55	35	33%	—	8	64	47	20
		PFFSB-157	Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	72	20
		PFFSB-197	Panels	24 x 48 x 5/8	0.55	40	44%	Yes*	8	64	72	20


Protectone*: A fire-resistive ceiling when used in applicable UL/ULC assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

Edge Details



Trim
9/16" EZ Stab
Elite Narrow



Trim
15/16" EZ Stab
Classic

Physical Data

MATERIAL

Mineral Fiber

FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type III, Form 2, Pattern D

ASTM E1264-23: Type A, Form A1.2, Pattern E

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year 104/90 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/warranty](https://www.certainteed.com/warranty).



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](https://www.certainteed.com)