

# Theatre® Black f

## FIBERGLASS SMOOTH PANEL

For theatres, salons or galleries, this fiberglass panel offers exceptional acoustic and aesthetic qualities.

### Features & Benefits

- Specifically developed to meet acoustical requirements for theater applications
- High humidity and inherent mold resistance are perfect for high volume spaces
- Dyed-matte finish provides extremely low surface gloss when compared to panels with a painted finish
- 30-Year System Warranty when installed with CertainTeed suspension systems

### Attributes



SAG RESISTANT



MOLD/MILDEW  
RESISTANT  
INHERENT



LR 0.03



RECYCLED  
CONTENT  
33%

## LEED® v4

| RECYCLED CONTENT | 33%                                                       |           |
|------------------|-----------------------------------------------------------|-----------|
|                  | PRE: 0%                                                   | POST: 33% |
| ✓                | MR: PBT Source Reduction (Healthcare)                     |           |
| ✓                | EQ: Acoustic Performance                                  |           |
| ✓                | EQ: Prereq. Min. Acoustic Performance (Schools)           |           |
| ✓                | MR: Sourcing Raw Materials                                |           |
| ✓                | MR: Environmental Product Declarations (EPDs)             |           |
| ✓                | MR: Construction and Demolition Waste Management Planning |           |
| ✓                | MR: Material Ingredients (HPDs)                           |           |

LEED® is a registered trademark of the U.S. Green Building Council.

### CERTIFICATIONS & PRODUCT DECLARATIONS



HPD AVAILABLE



EPD AVAILABLE




## Theatre® Black f

|                                                                                   |         |            | FORMAT | DIMENSIONS (IN.) | NRC  | CAC | RECYCLED CONTENT | PIECES/CARTON | SQ. FT./CARTON | LBS./CARTON | CARTONS/PALLET |
|-----------------------------------------------------------------------------------|---------|------------|--------|------------------|------|-----|------------------|---------------|----------------|-------------|----------------|
| Trim                                                                              |         |            |        |                  |      |     |                  |               |                |             |                |
|  | NRC .95 | 1942-THB-5 | Panels | 24 x 24 x 1      | 0.95 | —   | 33%              | 24            | 96             | 34          | 14             |
|                                                                                   |         | 1940-THB-5 | Panels | 24 x 48 x 1      | 0.95 | —   | 33%              | 12            | 96             | 34          | 14             |
|                                                                                   | NRC .80 | 1912-THB-5 | Panels | 24 x 24 x 5/8    | 0.80 | —   | 33%              | 32            | 128            | 22          | 18             |
|                                                                                   |         | 1910-THB-5 | Panels | 24 x 48 x 5/8    | 0.80 | —   | 33%              | 16            | 128            | 22          | 18             |


CAC range of 20-25 achieved with CAC foil backing. CAC Foil Backing is available for the entire Theatre Black f line as a special order.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

## Edge Details



Trim  
9/16" EZ Stab  
Elite Narrow



Trim  
15/16" EZ Stab  
Classic

## Physical Data

### MATERIAL

Fiberglass

### FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

### MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

### MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

### WARRANTY

10-year 104/95 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certaanteed.com/warranty](https://www.certaanteed.com/warranty)

### ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type XII, Form 2, Pattern G

ASTM E1264-23: Type B, Form B2, Pattern G



## CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM  
20 Moores Road, Malvern, PA 19355 800-233-8990 [certaanteed.com](https://www.certaanteed.com)