

Versatone[™]

FIBERGLASS TEXTURED PANEL

A high NRC fiberglass panel ideally suited for environments where economical installation, VOC compliance and low maintenance are primary considerations.

Features & Benefits

- VOC compliant to CDPH v1.2, 2017
- Complies with LEED v4 for Schools classroom acoustics prerequisite
- Embossed PVC-vinyl facer on fiberglass
- Excellent sound absorption
- High humidity resistance
- Ideal for economical installation and low maintenance environments
- 30-Year System Warranty when installed with CertainTeed suspension systems

Attributes







MOLD/MILDEW RESISTANT INHERENT



LR 0.73-0.79



RECYCLED CONTENT 35%



EMISSION COMPLIANT CERTIFIED



WASHABLE

LEED® v4

DECYCLED CONTENT	35%		
RECYCLED CONTENT	PRE: 0%	POST: 35%	

- MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- MR: Environmental Product Declarations (EPDs)
- MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



Versatone™

Colors



Versatone Black Astra		FORMAT	DIMENSIONS (IN.)	NRC	CAC	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET	
Trim							'					
NRC.70	R 1532	2-AST-5	Panels	24 x 24 x 5/8	0.70	_	_	35%	32	128	22	18
	1530	0-AST-5	Panels	24 x 48 x 5/8	0.70	_	_	35%	16	128	22	18
Versatone White Astra		FORMAT	DIMENSIONS (IN.)	NRC	CAC	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET	
Trim												
NRC .70		2-AST-1	Panels	24 x 24 x 5/8	0.70	-	0.78	35%	32	128	22	18
	1530	0-AST-1	Panels	24 x 48 x 5/8	0.70	_	0.78	35%	16	128	22	18
Versatone White Stipple												
Versatone Wh	ite Stip	ple	FORMAT	DIMENSIONS (IN.)	NRC	CAC	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
Versatone Wh	ite Stip	ple	FORMAT		NRC	CAC	LR					
	Q 1533	ple 2-STP-1	FORMAT Panels		NRC	CAC —	LR 0.73					
	0 153.			(IN.)				CONTENT	CARTON	CARTON	CARTÓN	PALLET
	2 1533 2 1533	2-STP-1 0-STP-1	Panels	(IN.) 24 × 24 × 5/8	0.70	-	0.73	CONTENT 35%	CARTON 32	128	CARTON 22	PALLET 18
Trim	2 1533 2 1533	2-STP-1 0-STP-1	Panels Panels	24 x 24 x 5/8 24 x 48 x 5/8 DIMENSIONS	0.70	-	0.73	35% 35% RECYCLED	32 16	128 128 SQ. FT./	22 22 LBS./	18 18 CARTONS/
Versatone Whi	2. 153. 153. te Vinta	2-STP-1 0-STP-1	Panels Panels	24 x 24 x 5/8 24 x 48 x 5/8 DIMENSIONS	0.70	-	0.73	35% 35% RECYCLED	32 16	128 128 SQ. FT./	22 22 LBS./	18 18 CARTONS/

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

Edge Details



Trim 15/16" EZ Stab Classic

Physical Data

MATERIAL

Fiberglass

FLAME SPREAD/SMOKE DEV. Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less Smoke Developed: 50 or less (Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type XII, Form 1, Pattern I ASTM E1264-23: Type B, Form B3, Pattern I

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment

WARRANTY

10-year 104/90 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

