



Report Number: 17-000915 Date Order Received: 05/16/2017

For the Account of:

Pollack & Associates 150 Varick Street New York, NY 10013

Client's Identification:	Biarritz 9262		

CERTIFICATE OF TESTING

TEST PERFORMED: NFPA 701 Standard Methods of Fire Test for Flame Propagation of Textiles and Films 2015 – Test #1

TEST RESULTS

Specimen	Mass Initial (g)	Mass Final (g)	Mass Loss (%)	Drip Burn (s)	Afterflame (s)
1	8.1	6.3	22	0.0	0.0
2	8.0	6.2	23	0.0	0.0
3	7.9	5.3	33	0.0	0.0
4	8.0	5.5	31	0.0	0.0
5	7.0	4.9	30	0.0	0.0
6	8.0	5.4	33	0.0	0.0
7	7.0	5.0	29	0.0	0.0
8	7.9	5.5	30	0.0	0.0
9	7.1	5.2	27	0.0	0.0
10	8.1	5.8	28	0.0	0.0
Average	7.7	5.5	29	0.0	0.0

Approximate weigi	nt (oz./sq. yd): 3.8	Standard Deviation: 3.7	Average + 3 SD: 40.1
Product Configura Conditioning: Intended End-use	_ ,	F for minimum 30 minutes	☐ 70 ±2°F & 65 ±2%RH for minimum 24 hours
 Where fra seconds Where th Individua Where th 	ed to be recorded; however, it is nagments or residues of specimen per specimen for the sample of 1 e average weight loss of the 10 s I specimens will be listed as a fail e specimens do not demonstrate	0 specimens, the material shall be re specimens in a sample is greater than lure if it exceeds mean + 3 SD	nber continue to burn for more than an average of 2
CONCLUSION	Based on the above Results and ⊠ Complies □ Does Not Comply	d Acceptance Criteria, the item tested	:t:
	certify that the above results were ndard stated above.	obtained after testing specimen in a	accordance with the procedures and equipment

553 76th Street, Byron Center, MI 49315

Authorized Signature

P: 616-559-6123 E: testlab@applied-textiles.com

Page 1 of 1

Date Order Completed: 05/25/2017