

## Specifications

### Billow

300187

#### Application

Walls

#### Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 52" (132cm)

Repeat: 22 1/4" V, 52" H

(57cm V, 132cm H)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

#### Price

Contact your sales representative for pricing.

#### Maintenance

W-Clean with water-based cleanser.

#### Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



# Specifications

Billow

300187

## Environmental

Greenguard Certified

Free of Intentionally Added PFAS

## Warranty

10 years.

© 2020 Knoll, Inc.

Complete product information at [knolltextiles.com](http://knolltextiles.com)

800.645.3943



001 Ice Breaker



002 Sandstorm



003 Delta



004 Heatwave



005 Gust



006 Nimbus



007 Sumi



008 Spellbound



009 Thunder



010 Ink Wash