

## Specifications

Cascade

by Trove

300148

### Application

Walls

### Characteristics

Content: 86% Thermoplastic Olefin, 14% Post-Industrial Recycled Glass

Finish: None

Backing: Polyester / Cellulose

Width: 50" (127cm)

Repeat: 60" V, 50" H

(152cm V, 127cm H)

Bolt Size: 50 yards (46 m)

Weight: 18 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

### Price

Contact your sales representative for pricing.

### Maintenance

W-Clean with water-based cleanser.

### Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



**Specifications**  
**Cascade**  
**by Trove**  
**300148**

**Environmental**

Greenguard Gold Certified  
LBC Red List Free  
Contains Recycled Content  
FR Free  
Free of Intentionally Added PFAS

**Warranty**

10 years.

© 2018 Knoll, Inc.

Complete product information at [knolltextiles.com](http://knolltextiles.com)  
800.645.3943



001 Sandalwood




002 Mirage



003 Echo



004 Pool



005 Aurora