

## Specifications

### Digital Ikat

300165

#### Application

Upholstered Walls, Walls

#### Characteristics

Content: 90% Polyester, 10% Thermoplastic Olefin

Finish: None

Backing: Acrylic

Width: 51" (130cm)

Repeat: 60" V, 51" H

(152cm V, 130cm H)

Bolt Size: 50 yards (46 m)

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: Korea

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

#### Price

Contact your sales representative for pricing.

#### Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

#### Testing

Flammability: ASTM E84 Adhered

ASTM E84 Unadhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications  
Digital Ikat  
300165

**Environmental**

Greenguard Gold Certified  
LBC Red List Free  
Free of Intentionally Added PFAS

**Warranty**


10 years.

© 2022 Knoll, Inc.

Complete product information at [knolltextiles.com](https://www.knolltextiles.com)  
800.645.3943



001 Unwind



002 Myth



003 Vista



004 Harmonic



005 Magnet