

Specifications**Drift****300144****Application**

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: 52% Pc Recycled Cellulose, 28% Cellulose, 20% Polyester

Width: 54" (137cm)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note: Slight variations in pattern are inherent to this textile.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Contact your sales representative for pricing.

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

**Testing**

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Drift

300144

Environmental

Greenguard Certified

Free of Intentionally Added PFAS

Warranty

10 years.

© 2020 Knoll, Inc.

Complete product information at knolltextiles.com

800.645.3943




001 Windswept




002 Sound Wave




003 Waterway



004 Palm




005 Basin



006 Storm



007 Flurry



008 Scale



009 Marine