

## Specifications

### Fragment

300240

#### Application

Walls

#### Characteristics

Content: 100% Vinyl

Finish: PFAS-Free Protective Topcoat

Backing: Polyester/Cotton Osnaburg

Width: 50" (127cm)

Bolt Size: 33 yards (30 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: Great Britain

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

#### Price

Contact your sales representative for pricing.

#### Maintenance

W-Clean with water-based cleanser.

#### Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



# Specifications

## Fragment

300240

### Environmental

Free of Intentionally Added PFAS

### Warranty

10 years.


© 2020 Knoll, Inc.

Complete product information at [knolltextiles.com](http://knolltextiles.com)


800.645.3943




001 Igloo




002 Pier




003 Scroll




004 Doeskin




005 Opal



006 Quartz




007 Mosaic




008 Bluestone




009 Penny



010 Artifact



011 Wolf



012 Basalt