

Specifications

Silhouette

300143

Application

Upholstered Walls, Walls

Characteristics

Content: 80% Polyester, 20% Rayon

Finish: None

Backing: None

Width: 67" (170cm)

Bolt Size: 27 yards (25 m)

Weight: 10.5 oz/ly (300 gr/lm)

Traffic: High Traffic

Country of Origin: Spain

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Contact your sales representative for pricing.

Maintenance

X-Vacuum or brush lightly to remove surface dust.

Testing

Acoustics: ASTM C423, 1.05 NRC

Flammability: ASTM E84 Adhered

ASTM E84 Unadhered

CAN ULC S102 Adhered

NFPA 701

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Silhouette
300143

Knoll Textiles

Environmental

Greenguard Gold Certified
LBC Red List Free
FR Free
Free of Intentionally Added PFAS

Warranty

10 years.

© 2019 Knoll, Inc.

Complete product information at [knolltextiles.com](https://www.knolltextiles.com)
800.645.3943




001 Mist



002 Stonewash




003 Whisper




004 Latte




005 Mulberry



006 Aloe



007 Splash



008 Cardinal



009 Dovetail



010 Foghorn



011 Crow